

REQUEST FOR
BID (RFB) FORM

MAILING ADDRESS:
MISSOURI DEPARTMENT OF TRANSPORTATION
GENERAL SERVICES, P.O. BOX 270
JEFFERSON CITY, MO 65102

REQUEST NO.	9-120509TV
DATE	April 27, 2012

SEALED BIDS, SUBJECT TO THE CONDITIONS ON ALL PAGES OF
THIS RFB WILL BE RECEIVED AT THIS OFFICE UNTIL

2:00 PM LOCAL TIME; May 9, 2012

AND THEN PUBLICLY OPENED AND READ FOR FURNISHING
THE FOLLOWING SUPPLIES OR SERVICES. SIGN AND RETURN
BEFORE TIME SET FOR OPENING.

BIDS TO BE BASED F.O.B.
MISSOURI DEPARTMENT OF TRANSPORTATION
Kansas City, MO

BUYER: Tom Veasman EMAIL: tom.veasman@modot.mo.gov

BUYER TELEPHONE: 573-522-4404

The purpose of this Request For Bids (RFB) is to accept bids for the utility service connections and grading at 3800 North Skiles Avenue, Kansas City, MO 64161 in accordance with the plans and as directed by the Facility Operations Supervisor. The project described as "Skiles Grading Project" shall be completed according to project drawings and specifications. The pricing being solicited under this RFB is for bids to be rendered to the Missouri Highways and Transportation Commission (hereinafter, "MHTC" or "Commission"), acting by and through its operating arm, the Missouri Department of Transportation (hereinafter, "MoDOT").

Notice to Contractors

This Request For Bid seeks bids from qualified organizations to provide utility service connections and grading at the location of the future Skiles Maintenance Facility. MoDOT will receive bids at the following mailing address: P.O. Box 270, Jefferson City, MO 65102-0270, or hand-delivered in a sealed envelope to the following physical address: General Services Procurement at 830 MoDOT Drive, Jefferson City, MO 65109 until 2:00 p.m., May 9, 2012. Bid forms and information may be obtained by contacting Tom Veasman at 573-522-4404, tom.veasman@modot.mo.gov, or electronically download them at no charge from http://modot.mo.gov/business/contractor_resources/FacilitiesConstructionandMaintenance.htm. Prevailing wage as established by the Missouri Department of Labor and Industrial Relations shall apply. Bid securities in the amount of 5% of the bid will be required to accompany bids. Bids must be made on forms provided by the Commission. The Commission reserves the right to reject any or all bids and to waive irregularity in the bids and the bidding. No bid may be amended or withdrawn after the bid is opened.

Written Questions: All written questions must be addressed to Tom Veasman no later than 2:00 p.m., Local Time, Wednesday, May 2, 2012 at the following mailing address: Missouri Dept. of Transportation, General Services Procurement Unit, P.O. Box 270, Jefferson City, MO 65102-0270 or by e-mail to tom.veasman@modot.mo.gov. Any questions received after this deadline will not be accepted. MoDOT may issue an addendum and post the responses to all questions on-line for vendors to retrieve. Responses to the questions will be posted on MoDOT's website at:

http://modot.mo.gov/business/contractor_resources/FacilitiesConstructionandMaintenance.htm

in the form of a written addendum. It is anticipated this addendum will be issued on Thursday, May 3, 2012. It is the sole responsibility of the Bidder to check for any and all addendums throughout the Bid process.

(SEE ATTACHED FOR TERMS, CONDITIONS, AND INSTRUCTIONS)

In compliance with the above Request For Bid, and subject to all conditions thereof, the undersigned bidder agrees to furnish and deliver any or all the items on which prices were bid within the timeframe specified herein.

Date: _____
Telephone No.: _____
Fax No.: _____
Federal I.D. No. _____
Email Address: _____

Firm Name: _____
Address: _____
By (Signature): _____
Type/Print Name _____

Is your firm MBE certified? Yes No

Title: _____
Is your firm WBE certified? Yes No

TABLE OF CONTENTS

DIVISION	PAGE
DIVISION 0-BIDDING AND CONTRACT INFORMATION	
FINAL CHECKLIST BEFORE SUBMITTING BID	1
NEWSPAPER ADVERTISEMENT Notice to Contractors	2
00100 BIDDER REQUIREMENTS	3
00301 BID FORM	9
00430 SUBCONTRACTOR LISTING	13
00600 BID BOND	14
DIVISION 1 – GENERAL REQUIREMENTS (BROAD SCOPE)	
01019 CONTRACT REQUIREMENTS	15
01039 COORDINATION AND MEETING REQUIREMENT	17
01300 SUBMITTAL REQUIREMENTS	20
01400 QUALITY CONTROL REQUIREMENTS	24
01500 CONSTRUCTION FACILITEIS AND TEMPORARY CONTROL REQUIREMENTS	26
01600 MATERIAL AND EQUIPMENT REQUIREMENT	28
01700 CONTRACT CLOSEOUT REQUIREMENT	30
JOB SPECIAL PROVISIONS and Soil Borings	34
Terms & Conditions	
Annual Wage Order #18 for Clay County	
Project Drawings (To be printed in ANSI D (22" x 34"). Half size of ANSI B (11" x 17") may suffice.)	

"EXCESSIVE UNEMPLOYMENT IS IN EFFECT"

During times of high unemployment, state law permits the Department's Division of Labor Standards to declare that excessive unemployment is in effect, allowing only workers from certain states to work on the Missouri's public works projects. Public works projects are construction projects funded wholly or partially from public funds, or are projects that benefit the public such as but not limited to schools, parks, fire houses, and government buildings. The excessive unemployment law does not apply to projects funded in part by Federal Funds.

Restrictive states have laws in place restricting Missouri workers to work on their public works projects. Workers from these states are also not allowed to work on Missouri's public works projects.

Only Missouri laborers and laborers from nonrestrictive states are allowed by law to be employed on Missouri's public works projects when the unemployment rate exceeds **5 percent** for two consecutive months. (See Sections **290.550 through 290.580 RSMo**). To file a complaint against a contractor for employing a worker from one of the restrictive states below on a Missouri public works project, submit the **complaint form** online for the Division to investigate.

Restrictive States- workers from these states are **NOT** allowed to be employed on Missouri public works projects: Alaska, Arizona, California, Colorado, Connecticut, Delaware, District of Columbia, Florida, Idaho, Illinois, Maine, Massachusetts, Mississippi, Montana, Nevada, New Jersey, North Dakota, South Dakota, and the U.S. Virgin Islands, West Virginia and Wyoming.

Non-Restrictive States- workers from these states are allowed to be employed on Missouri public works projects: Alabama, Arkansas, Georgia, Hawaii, Indiana, Iowa, Kansas, Kentucky, Louisiana, Maryland, Michigan, Minnesota, Nebraska, New Hampshire, New Mexico, New York, North Carolina, Ohio, Oklahoma, Oregon, Pennsylvania, Rhode Island, South Carolina, Tennessee, Texas, Utah, Vermont, Virginia, Washington and Wisconsin.

FINAL CHECKLIST BEFORE SUBMITTING BID

- ____ 1. Complete the Bid Form by filling in the total dollar amount of the bid and the total dollar amount for alternate bids; listing any addenda which may have been issued; filling in the dollar amount of the bidder's check or Bid Bond, sign the proper signature line, and supply the required information in connection with the signature for the individual bidder, joint adventurer, or corporation.
- ____ 2. Submit Bid Bond executed by the bidder and surety. Bidders are required to use the Bid Bond furnished by the Commission or attach cashier's check to Bid Bond form. Personal checks are not accepted.
- ____ 3. Complete Subcontractor section by listing major subcontractor(s) and general supervisor(s), sign as required.
- ____ 4. Complete Vendor Information and Preference Certification Form.
- ____ 5. If addenda(s) are issued attach to the back of the bid package.

NEWSPAPER ADVERTISEMENT

Notice to Contractors

MoDOT will receive bids at its General Services, Procurement section, 830 MoDOT Drive, Jefferson City, MO until 2:00 p.m., May 9, 2012 for the grading/utility service connections at the location of 3800 North Skiles Avenue, Kansas City, MO 64161. Contact Tom Veasman at 573-522-4404 or Tom.Veasman@modot.mo.gov to obtain plans, forms, and information or download them at no charge from <http://www.modot.org/gsbidding/>.

BIDDER REQUIREMENTS**1. SCOPE OF WORK**

The work shall consist of; removing trees and undergrowth, grading the parcel and removing excess soil, building a storm water detention pond with a drainage structure and pipe and providing utility stub-in work for gas, power, water, sewer, phone and data service line. Add alternate work shall consist of furnishing and placing a 9 inch thick crushed rock surface.

2. BID INSTRUCTIONS

In order to receive consideration, bids must be made in strict accordance with the following.

- A. Make bids, upon the forms provided herein, properly signed and with all items filled out. Do not change the wording of the bid form and do not add words to the bid form. Unauthorized conditions, limitations or provisions attached to the bid will be cause for rejection of the bid.
- B. No telegraphic bid or telegraphic modification of a bid will be considered. No bids received after the time fixed for receiving them will be considered. Late bids will be returned to the bidder unopened.
- C. Address bids to the Missouri Department of Transportation, and deliver to the address given in the Invitation for Bid, on or before the day and hour set for opening the bids. Enclose each bid in a sealed envelope bearing the title of the Work, the name of the bidder, and the date and hour of the bid opening. Submit only the original signed copy of the bid. It is the sole responsibility of the bidder to see that the bid is received on time.

3. INVOICING AND PAYMENT

- A. Each invoice should be itemized in accordance with items listed on the contract in accordance with Section 01019, Contract Considerations, Applications for Payment provisions. Failure to comply with this requirement may delay processing of invoices for payment.
- B. Unless otherwise provided for in the solicitation documents, payment for all equipment, supplies, and/or services required herein shall be made in arrears. The Commission shall not make any advance deposits.
- C. The Commission assumes no obligation for equipment, supplies, and/or services shipped or provided in excess of the quantity ordered. Any authorized quantity is subject to the Commission's rejection and shall be returned at the Contractor's expense.
- D. The Commission reserves the right to purchase goods and services using the state-purchasing card.

4. EXAMINATION OF DOCUMENTS AND SITE OF WORK

- A. Before submitting a bid, each bidder shall examine the Drawings carefully, read the Specifications and all other proposed Contract Documents, and visit the site of the work. Each bidder shall fully inform themselves, prior to bidding, as to existing conditions and limitations under which the Work is to be performed and shall include in his bid a sum to cover the cost of items necessary to perform the Work, as set forth in the proposed Contract Documents. No allowance will be made to a bidder because of lack of such examination or knowledge. The submission of a bid will be considered conclusive evidence that the bidder has made such examination.
- B. The contract price shall include any necessary permits and licenses required by law incidental to the work. Local ordinances requiring building permits are not applicable to the state. Contractor will comply with local laws involving safety in the prosecution of the work.

5. INTERPRETATION

No oral interpretations will be made to any bidder as to the meaning of the plans and specifications or the acceptability of alternate products, materials, form or type of construction. Every request for interpretation shall be made in writing and submitted with all supporting documents not less than eight (8) days before opening of bids. The request shall be sent directly to the Senior Facilities Designer. Every interpretation made to a bidder will be in the form of an addendum and will be sent as promptly as is practicable to all persons to whom plans and specifications have been issued. All such addenda shall become part of the contract documents.

6. PROOF OF COMPETENCY OF BIDDER

A bidder may be required to furnish evidence, satisfactory to the Commission, that he and his proposed subcontractor(s) have sufficient means and experience in the types of work called for to assure completion of the Contract in a satisfactory manner.

7. WITHDRAWAL OF BIDS

After the bid opening, a vendor may be permitted to withdraw a bid prior to award at the sole discretion of the division if there is a verifiable error in the bid and enforcement of the bid would impose an unconscionable hardship on the vendor. This withdrawal will be considered only after receipt of a written request and supporting documentation from the vendor. Withdrawal shall be the vendor's sole remedy for an error other than an obvious clerical error. Withdrawal of a bid may result in forfeiture of the bid bond.

8. AWARD OR REJECTION OF BIDS

The Contract, if awarded, will be made on an "All or None" basis using the "lowest and best" principle of award, subject to the Commission's right to reject any or all bids and to waive informality and irregularity in the bids and in the bidding.

9. CONTRACT DOCUMENTS

The contract expresses the complete agreement of the parties and performance shall be governed solely by the specifications and requirements contained therein. Any change, whether by modification and/or supplementation, must be accomplished by a formal contract amendment signed and approved by and between the duly authorized representative of the Contractor and the duly authorized representative of the Commission, by a modified purchase order prior to the effective date of such modification. The Contractor expressly and explicitly understands and agrees that no other method and/or no other document, including correspondence, acts, and oral communications by or from any person, shall be used or construed as an amendment or modification.

10. SUBMITTALS

Review of Submittals. The Architect/Engineer/Designer review of submittals is only for the limited purpose of checking for conformance with information given and seeing if they conform to design intent. The General Services Facilities Manager is not responsible for determining the accuracy of measurements and completeness of details, for verifying quantities, or for checking fabrication or installation procedures. The General Services Facilities Manager's review does not relieve the contractor of his or her responsibilities under the contract documents. The submittal process shall be carried out as outlined in Section 01300, Submittals.

11. WORK QUALITY

- A. Inspection of Work. The General Services Facility Operations Supervisor or designated representative shall be permitted to inspect all work, materials, payrolls, records of personnel, invoices of materials, and other data and records relating to the work. If requested by the General Services-Facility Operations Supervisor or designated representative, the contractor shall at any time before final acceptance of the work uncovers any portion of the finished work as directed for inspection. After examination, the contractor shall restore said portions of the work to the standards required by the contract. Should the work thus exposed and examined prove acceptable, the actual cost of uncovering, removing and replacing shall be paid by the Commission. Should the work so exposed and examined prove unacceptable, the uncovering, removing and replacing shall be at the expense of the contractor.
- B. Defective Work. All work which has been rejected shall be remedied, or if necessary, removed and replaced in an acceptable manner by the contractor at its expense. If the contractor fails to remedy or replace such defective work immediately after receiving written notice from the General Services-Facility Operations Supervisor or designated representative, the Commission may employ labor to correct the defective work, and the cost incurred in making such corrections shall be deducted from the payment due or to become due the contractor under this contract.
- C. Contractor will provide a one-year warranty for parts and labor on all building material, and equipment or a standard manufacturer's warranty whichever is greater. All warranties, including extended service agreements shall begin upon MoDOT's written acceptance of the punch list items.
- D. Contractor's Responsibility for Work. Until the General Services-Facility Operations Supervisor or designated representative, accepts the work, it shall be in the custody and under the charge and care of the contractor. Contractor

shall rebuild, repair, restore or make good at its own expense any lost or stolen Commission-owned material and all injuries or damages to any portion of the work caused by action of the elements or from any other reason before its completion and final acceptance. Issuance of a payment estimate on any part of the work done will not be considered as final acceptance of any work completed up to that time.

- E. Preservation of Utilities and Monuments. The contractor shall be responsible for the preservation of all public and private utilities, wires, lines, pipes, poles, cables, and conduit at the site of the work and shall use every precaution necessary to prevent damage or injury thereto. The contractor shall not disturb or damage any land monument or property landmark until an authorized agent has witnessed or otherwise referenced, their location and shall not remove them until directed by General Services Facilities Manager.
- F. Cooperation with Other Contractors. The contractor shall arrange its work so as not to interfere with the operations of other contractors of the Commission which might be engaged in performing adjacent or nearby work. Whenever work being done by other contractors is contiguous or related to the work involved in this contract, the respective rights of the various contractors will be determined by the General Services-Facility Operations Supervisor or designated representative in order to secure the completion of the work under all contracts in general harmony.
- G. The contractor will be required to remove from the Commission's property all debris.
- H. Temporary Suspension of Work. The General Services-Facility Operations Supervisor or designated representative shall have authority to suspend work, wholly or in part, for such period or periods of time as he may deem necessary when weather or other conditions are such that in the opinion of the General Services-Facility Operations Supervisor or designated representative the work may be done at a later time with advantage to the Commission or for failure on the part of the contractor to comply with any of the provisions of the contract. The contractor may suspend work for reasonable cause with written approval of the General Services-Facility Operations Supervisor or designated representative. Liquidated damages shall not accrue during the period in which work is suspended with the approval of the General Services-Facility Operations Supervisor or designated representative, however, if the suspension is because of the contractor's failure to comply to any of the provisions of the contract, the contractor shall not be entitled to an extension of completion time nor to a waiver of liquidated damages. In the event work is suspended, the contractor shall store all materials in a manner that will protect them from damage, and shall take every precaution to prevent damage or deterioration of, the portions of the work completed. If work has been discontinued for any reason, the contractor shall give the General Services-Facility Operations Supervisor or designated representative written notice at least forty-eight (48) hours before resuming operations.

12. CHANGE ORDERS

- A. General. All departures from the plans and specifications will be considered unauthorized unless, before proceeding with the work, the contractor has had delivered to it a change order, signed by the General Services-Facility Operations Supervisor or designated representative, authorizing and directing such changes or departures. All unauthorized work shall be at the contractor's expense and the General Services-Facility Operations Supervisor or designated representative may order such unauthorized work removed and replaced at the contractor's expense.
- B. Overhead and Profit on Change Orders. The percentages for overhead and profit charged on Change Orders and Field Work Authorizations shall be negotiated and may vary according to the nature, extent and complexity of the work involved. However, the overhead and profit for the contractor or subcontractor actually performing the work shall not exceed 15%. When one or more tiers of subcontractors are used, in no event shall any contractor or subcontractor receive as overhead and profit more than 7% of the cost of the work performed by any of his subcontractors. In no case shall the total overhead and profit paid by the owner on any change order exceed twenty five percent (25%) of the cost of materials, labor and equipment necessary to put the change order work in place.
- C. Contractor's Procedure for Claims. If the contractor considers additional compensation may be due for work or material not clearly covered in the contract or ordered in writing by the General Services-Facility Operations Supervisor or designated representative as extra work, or if additional compensation may be requested beyond the scope of such provisions, the contractor shall notify the General Services-Facility Operations Supervisor or designated representative in writing of the intention to make a claim before beginning the work in question. If notification is not given and the General Services-Facility Operations Supervisor or designated representative is not afforded proper facilities by contractor to provide necessary inspection and for keeping strict account of actual cost, the contractor agrees to waive any claims for additional compensation. Notice by the contractor, and the fact that the General Services-Facility Operations Supervisor or designated representative has kept account of the cost shall not be construed as substantiating

the validity of the claim. The contractor shall file a written notice of claim for additional compensation in triplicate within 60 days after completing the work in question.

- a. If the claim is against the Commission, the notice of claim shall be personally delivered, or sent by certified mail to the office of the Secretary of the Commission in Jefferson City, Missouri. All notices of claims shall contain an itemized statement showing completely and fully the items and amounts forming the basis of the claim.
- b. Any claim or an item of any claim, not included in the notice and statement, or any claim included but not clearly defined and specifically set out and itemized or any claim not filed within the time and in the manner provided, shall be forever waived and shall neither constitute the basis of nor be included in any legal action, counterclaim, set-off, or arbitration.
- c. All claims filed with Missouri Highway and Transportation Commission's Secretary will be forwarded to the Missouri Department of Transportation's Claims Committee.

13. GENERAL PERFORMANCE

- A. Bidders are encouraged to obtain minority business enterprise (MBE) and women business enterprise (WBE) participation in this work through the use of subcontractors, suppliers, joint ventures, or other arrangements that afford meaningful participation for M/WBEs. Bidders are encouraged to obtain 10% MBE and 5% WBE participation.
- B. This work is to be performed under the general supervision and direction of the Missouri Department of Transportation (MoDOT) and, if awarded any portion of the work, the Contractor agrees to furnish at his own expense all labor and equipment required to complete the work, it being expressly understood that this solicitation is for completed work based upon the price(s) specified and is not a solicitation for rental of equipment or employment of labor by MoDOT, and MoDOT is to have no direction or control over the employees used by the Contractor in performance of the work.

14. REMEDIES AND RIGHTS

- A. No provision in the contract shall be construed, expressly or implied, as a waiver by the MHTC of any existing or future right and/or remedy available by law in the event of any claim by the MHTC of the Contractor's default or breach of contract.
- B. The Contractor agrees and understands that the contract shall constitute an assignment by the Contractor to the MHTC of all rights, title and interest in and to all causes of action that the Contractor may have under the antitrust laws of the United States or State of Missouri for which causes of action have accrued or will accrue as the result of or in relation to the particular equipment, supplies, and/or services purchased or produced by the Contractor in the fulfillment of the contract with the MHTC.
- C. In the event a Contractor becomes involved in, or is threatened with, litigation with a subcontractor or supplier as a result of such direction, the Contractor may request MoDOT to enter into such litigation to protect the interests of the MHTC, and, in addition, the Contractor may request the United States to enter into such litigation to protect the interests of the United States.

15. INVENTIONS, PATENTS, AND COPYRIGHTS

The Contractor shall defend, protect, and hold harmless the MHTC, its officers, agents, and employees against all suits of law or in equity resulting from patent and copyright infringement concerning the Contractor's performance or products produced under the terms of the contract.

16. INSPECTION AND ACCEPTANCE

- A. No equipment, supplies, and/or services received by MoDOT pursuant to a contract shall be deemed accepted until MoDOT has had reasonable opportunity to inspect said equipment, supplies, and/or services.
- B. All equipment, supplies, and/or services which do not comply with the specifications and/or requirements or which are otherwise unacceptable or defective may be rejected. In addition, all equipment, supplies, and/or services which are discovered to be defective or which do not conform to any warranty of the Contractor upon inspection (or at any later time if the defects contained were not reasonably ascertainable upon the initial inspection) may be rejected.

- C. The MHTC reserves the right to return any such rejected shipment at the Contractor's expense for full credit or replacement and to specify a reasonable date by which replacements must be received.
- D. The MHTC's right to reject any unacceptable equipment, supplies, and/or services shall not exclude any other legal, equitable or contractual remedies the MHTC may have.

17. DEFINITIONS

Architect/Engineer/Designer: When the term "Architect or Engineer or Designer" is used herein, it shall refer to Dennis Francis, 816-607-2235(office).

MoDOT Inspector or Facility Operations Supervisor: When the term "MoDOT Inspector or Facility Operations Supervisor" is used herein, it shall refer to those MoDOT individuals authorized to perform site inspections by Marvin Wallace, [Facility Operations Supervisor] Kansas City District, General Services Division, 816-347-4106(Office), 816-365-9946(Cell),

Owner: When the term "Owner" is used herein, it shall refer to Missouri Department of Transportation (MoDOT).

VENDOR INFORMATION & PREFERENCE CERTIFICATION FORM

Vendor Information

All bidders must furnish ALL applicable information requested below

Vendor Name/Mailing Address: Email Address:	Vendor Contact Information (including area codes): Phone #: Cellular #: Fax #:									
Printed Name of Responsible Officer or Employee:	Signature:									
For Corporations - State in which incorporated:	For Others - State of domicile:									
If the address listed in the Vendor Name/Mailing Address block above is not located in the State of Missouri, list the address of Missouri offices or places of business: If additional space is required, please attach an additional sheet and identify it as Addresses of Missouri Offices or Places of Business.										
M/WBE INFORMATION: List all certified Minority or Women Business Enterprises (M/WBE) utilized in the fulfillment of this bid. Include percentages for subcontractors and identify the M/WBE certifying agency: <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left; border-bottom: 1px solid black;"><u>M/WBE Name</u></th> <th style="text-align: left; border-bottom: 1px solid black;"><u>Percentage of Contract</u></th> <th style="text-align: left; border-bottom: 1px solid black;"><u>M/WBE Certifying Agency</u></th> </tr> </thead> <tbody> <tr> <td style="border-bottom: 1px solid black;"> </td> <td style="border-bottom: 1px solid black;"> </td> <td style="border-bottom: 1px solid black;"> </td> </tr> <tr> <td style="border-bottom: 1px solid black;"> </td> <td style="border-bottom: 1px solid black;"> </td> <td style="border-bottom: 1px solid black;"> </td> </tr> </tbody> </table> If additional space is required, please attach an additional sheet and identify it as M/WBE Information		<u>M/WBE Name</u>	<u>Percentage of Contract</u>	<u>M/WBE Certifying Agency</u>						
<u>M/WBE Name</u>	<u>Percentage of Contract</u>	<u>M/WBE Certifying Agency</u>								

Preference Certification

All bidders must furnish ALL applicable information requested below

GOODS/PRODUCTS MANUFACTURED OR PRODUCED IN USA: If any or all of the goods or products offered in the attached bid which the bidder proposes to supply to the MHTC are <u>not</u> manufactured or produced in the "United States", or imported in accordance with a qualifying treaty, law, agreement, or regulation, list below, by item or item number, the country other than the United States where each good or product is manufactured or produced.	
Item (or item number)	Location Where Item is Manufactured or Produced
If additional space is required, please attach an additional sheet and identify it as Location Products are Manufactured or Produced.	
MISSOURI SERVICE-DISABLED VETERAN BUSINESS: Please complete the following if applicable. Additional information may be requested if preference is applicable. See below definitions for qualification criteria: Service-Disabled Veteran is defined as any individual who is disabled as certified by the appropriate federal agency responsible for the administration of veterans' affairs. Service-Disabled Veteran Business is defined as a business concern: <ol style="list-style-type: none"> a. Not less than fifty-one (51) percent of which is owned by one or more service-disabled veterans or, in the case of any publicly owned business, not less than fifty-one (51) percent of the stock of which is owned by one or more service-disabled veterans; and b. The management and daily business operations of which are controlled by one or more service-disabled veterans. 	
<u>Veteran Information</u>	<u>Business Information</u>
Service-Disabled Veteran's Name (Please Print)	Service-Disabled Veteran Business Name
Service-Disabled Veteran's Signature	Missouri Address of Service Disabled Veteran Business

00301

BID FORM

To: The Missouri Highway and Transportation Commission
PO Box 270
Jefferson City, Missouri 65102

1. The undersigned, having examined the proposed Contract Documents titled: **9-120509TV – Skiles Grading Project** and having visited the site and examined the conditions affecting the work, hereby proposes and agrees to furnish all labor, materials, equipment and everything which may be necessary or incidental thereto, as proposed by said Contract Documents, all to the satisfaction of the General Services-Facility Operations Supervisor or designated representative of the Missouri Department of Transportation and the Missouri Highway and Transportation Commission, for the stipulated sum of:

6039901	Utility Connection – Water	lump sum	Total \$ _____.
	Utility Connection - Fire Line and Fire Hydrant	lump sum	Total \$ _____.
6039921	Utility Connection – Sewer	lump sum	Total \$ _____.
6039931	Utility Connection – Gas	lump sum	Total \$ _____.
9019901	Utility Connection - Power	lump sum	Total \$ _____.
9019901(1)	Utility Connection - Phone / Data	lump sum	Total \$ _____.
6274000	Contractor Surveying and Staking	lump sum	Total \$ _____.
2022010	Removal of Improvements	lump sum	Total \$ _____.
2013000	Clearing and Grubbing	\$ _____ X Qty 1 acre =	\$ _____.
2031000	Class A Excavation	\$ _____ X Qty. 12,838 cu. yd. =	\$ _____.
2036000	Compacting Embankment	\$ _____ X Qty. 5,219 cu. yd. =	\$ _____.
6096030A	Furnishing Type 3 Rock Ditch Liner	\$ _____ X Qty. 154 cu. yd. =	\$ _____.
6096040	Placing Type 3 Rock Ditch Liner	\$ _____ X Qty. 154 cu. yd. =	\$ _____.
6096050	Bedding for Rock Ditch Liner	\$ _____ X Qty. 56 cu. yd. =	\$ _____.
6117020	Erosion Control Geotextile	\$ _____ X Qty. 252 sq. yd. =	\$ _____.
6141021	Grate and Bearing Plate (3'x 2')	\$ _____ X Qty. 1 each =	\$ _____.
6161005	Construction Signs	\$ _____ X Qty. 152 sq. ft. =	\$ _____.
7250318A	18" Group B pipe	\$ _____ X Qty. 125 lin. ft. =	\$ _____.
7311032	3'x2' precast Drop Inlet	\$ _____ X Qty. 9 feet =	\$ _____.
8061016	Sediment Removal	\$ _____ X Qty. 22 cu. yd. =	\$ _____.
8061019	Silt Fence	\$ _____ X Qty. 1312 lin. ft. =	\$ _____.

8061022 Type II Ditch Check \$ _____ X Qty. 4 each = \$ _____
 9019903 3/4" conduit, explosion proof \$ _____ X Qty. 85 lin. ft. = \$ _____
 9029903 1" conduit Schedule 80 \$ _____ X Qty. 1850 lin. ft. = \$ _____
 6181000 Mobilization (2%) lump sum \$ _____

BASE BID TOTAL \$ _____

ALTERNATE A:

3039905 Crushed Rock Base, 9-inch thick, 3" rock \$ _____ X Qty. 1803 cu. yd. = \$ _____

ALTERNATE A TOTAL \$ _____

ALTERNATE B:

3039905 Crushed Rock Base, 9-inch thick, 3" rock \$ _____ X Qty. 1803 cu. yd. = \$ _____

ALTERNATE B TOTAL \$ _____

2. The undersigned, acknowledges having examined and being familiar with the contract documents including the drawings, the Instructions to Bidders, General Conditions, Supplementary Conditions and the body of technical specifications.
3. The undersigned acknowledges receipt of Addenda number _____ through _____ inclusive.
4. Enclosed with this bid is bid security in the amount of not less than 5% of the bidder's proposed Contract Sum, the amount being _____ DOLLARS (\$ _____).

IF AN INDIVIDUAL

 Name of individual

 Residence address

 Social Security Number

 Telephone Number

 Firm Name, If Any

 Address for communications

 Signature

IF A PARTNERSHIP

Name of Partnership

(State Name and Residence Address of All Partners)

Partner

Residence Address

Partner

Residence Address

Address for Communications

Federal Tax I.D. Number

Telephone Number

Signature of Either Partner

IF A CORPORATION

Name of Corporation

Incorporated under the laws of the
State of _____

Name and Title of Officer

Corporate License No. _____
(If a corporation organized in a state other than
Missouri, attach Certificate of Authority to do
business in the State of Missouri.)

Signature of officer

Federal Tax I.D. Number

Address for Communications

(ATTEST)

Telephone Number

(SEAL)

Secretary

(Each bidder must complete the Bid Form by signing in the proper signature line above and by supplying the required information called for in connection with the signature. The information called for is necessary in the proper preparation of the contract and performance bond.)

00430

SUBCONTRACTOR LISTING

1. For portions of Work equaling or exceeding 1% of the total proposed Contract Sum, the undersigned proposes to use the following subcontractors. Except as otherwise approved by the Owner, the undersigned proposes to perform all other portions of the Work with his own forces.

2. Portion of the Work:	Subcontractor name and address:
_____	_____
_____	_____
_____	_____
_____	_____
_____	_____
_____	_____
_____	_____
_____	_____
_____	_____
_____	_____

USE ADDITIONAL SHEETS
IF REQUIRED

BIDDER:

PROVIDE SIGNATURE
IDENTICAL TO THAT
SHOWN ON THE BID FORM

by _____

00600

BID BOND

KNOW ALL MEN BY THESE PRESENTS, that we _____,
as Principal, and _____,
as Surety, are held firmly bound unto the State of Missouri (acting by and through the Missouri Highway and
Transportation Commission) in the penal sum of

_____ Dollars

(\$ _____), to be paid to the State of Missouri, or the Missouri Highway and Transportation
Commission, to be credited to the State Road Fund and Principal and Surety binding themselves, their heirs,
executors, administrators, successors and assigns, jointly and severally, firmly by these presents.

Sealed with our seals and dated this _____ day of _____, 20_____

THE CONDITION OF THIS OBLIGATION is such that:

WHEREAS, the Principal is submitting herewith a bid to the Missouri Highway and Transportation Commission on
Route(s) _____,
in _____ County(ies), Project(s) _____,
for construction or improvement as set out in said bid.

NOW THEREFORE, if the Missouri Highway and Transportation Commission shall accept the bid of the Principal,
and if said Principal shall properly execute and deliver to the Missouri Highway and Transportation Commission the
Contract, Contract Bond, Specifications and evidence of insurance coverage in compliance with the requirements of
the Bid, to the satisfaction of the Missouri Highway and Transportation Commission, then this obligation shall
be void and of no effect, otherwise to remain in full force and effect.

In the event the said Principal shall, in the judgment of the Missouri Highway and Transportation Commission, fail to
comply with any requirement as set forth in the preceding paragraph, then the State of Missouri, acting through the
Missouri Highway and Transportation Commission, shall immediately and forthwith be entitled to recover the fees,
and any other expense of recovery.

Principal

Surety

By _____

Attorney in Fact (SEAL)

Attest: (CORPORATE SEAL)

Corporate Secretary

Note: This bond must be executed by the Principal and by a Corporate Surety authorized to conduct
surety business in the State of Missouri.

END OF SECTION

CONTRACT REQUIREMENTS

PART 1 GENERAL

1.1 SECTION INCLUDES

- A. Schedule of values.
- B. Application for payment.
- C. Change procedures.
- D. Alternatives.

1.2 RELATED SECTIONS

- A. Section 01600 - Material and Equipment: Product substitutions.

1.3 SCHEDULE OF VALUES

- A. Submit a printed schedule on Contractor's standard form. Electronic media printout will be considered.
- B. Submit Schedule of Values in duplicate within 20 days after date of Owner-Contractor Agreement.
- C. Revise schedule to list approved Change Orders, with each Application for Payment.

1.4 APPLICATIONS FOR PAYMENT

- A. Submit four copies of each application on Contractor's electronic media driven form.
- B. Content and Format: Utilize Schedule of Values for listing items in Application for Payment.
- C. Payment Period: 30 days.
- D. Submit waiver of liens from vendors.
- E. Include an updated construction progress schedule.
- F. Certified payroll records.

1.5 CHANGE PROCEDURES

- A. The Architect/Engineer/Designer may issue a Notice of Change that includes a detailed description of a proposed change with supplementary or revised Drawings and specifications, a change in Contract Time for executing the change with a stipulation of any overtime work required.
- B. The Contractor may propose changes by submitting a request for change to the Architect/Engineer/Designer describing the proposed change and its full effect on the Work. Include a statement describing the reason for the change, the effect on the Contract Sum/Price and Contract Time, and a statement describing the effect on Work by the MoDOT District or other Contractors.
- C. Stipulated Sum/Price Change Order: Based on Notice of Change and Contractor's fixed price quotation or Contractor's request for a Change Order as approved by Architect/Engineer/Designer.
- D. Construction Change Directive: Architect/Engineer/Designer may issue a directive instructing the Contractor to proceed with a change in the Work, for subsequent inclusion in a Change Order. Document will describe changes in the Work, and designate method of determining any change in Contract Sum/Price or Contract Time. Promptly execute the change.

- E. Time and Material Change Order: Submit itemized account and supporting data after completion of change, within time limits indicated in the Conditions of the Contract. Architect/Engineer/Designer will determine the change allowable in Contract Sum/Price and Contract Time as provided in the Contract Documents.
- F. Maintain detailed records of work done on Time and Material basis. Provide full information required for evaluation of proposed changes, and to substantiate costs for changes in the Work.
- G. Execution of Change Orders: Architect/Engineer/Designer will issue Change Orders for signatures of parties as provided in the Conditions of the Contract.

1.6 DEFECT ASSESSMENT

- A. Replace the Work, or portions of the Work, not conforming to specify requirements.
- B. If, in the opinion of the Architect/Engineer/Designer, it is not practical to remove and replace the Work, the Architect/Engineer/Designer will direct an appropriate remedy or adjust payment.

1.7 ALTERNATIVES

- A. Accepted Alternatives will be identified in Owner-Contractor Agreement.

END OF SECTION

COORDINATION AND MEETING REQUIREMENT

PART 1 GENERAL

1.1 SECTION INCLUDES

- A. Coordination and project conditions.
- B. Field engineering.
- C. Preconstruction meeting.
- D. Site mobilization meeting.
- E. Progress meetings.
- F. Pre-installation meetings.
- G. Equipment electrical characteristics and components.
- H. Examination.
- I. Preparation.
- J. Cutting and Patching.
- K. Alteration project procedures.

1.2 COORDINATION AND PROJECT CONDITIONS

- A. Coordinate scheduling, submittals, and Work of the various sections of the Project Manual to ensure efficient and orderly sequence of installation of interdependent construction elements.
- B. Verify utility requirements and characteristics of operating equipment are compatible with building utilities. Coordinate work of various sections having interdependent responsibilities for installing, connecting to and placing in service, such equipment.
- C. Coordinate space requirements, supports, and installation of mechanical and electrical Work, which are indicated diagrammatically on Drawings. Follow routing shown for pipes, ducts, and conduit, as closely as practicable; place runs parallel with lines of building. Utilize spaces efficiently to maximize accessibility for other installations, for maintenance, and for repairs.
- D. In finished areas, except as otherwise indicated, conceal pipes, ducts and wiring within the construction. Coordinate locations of fixtures and outlets with finish elements.
- E. Coordinate completion and clean up of Work of separate sections in preparation for Substantial Completion.
- F. After Owner occupancy of premises, coordinate access to site for correction of defective Work and Work not in accordance with Contract Documents, to minimize disruption of Owner's activities.

1.3 FIELD ENGINEERING

- A. Employ a Land Surveyor registered in the State of Missouri and acceptable to Architect/Engineer/Designer.
- B. Owner will locate and protect survey control and reference points.
- C. Control datum for survey is that established by Owner provided survey.
- D. Verify setbacks and easements; confirm drawing dimensions and elevations.
- E. Provide field engineering services. Establish elevations, lines and levels, utilizing recognized engineering survey practices.

1.4 PRECONSTRUCTION MEETING

- A. Architect/Engineer/Designer will schedule a meeting after Notice of Award.

- B. Attendance Required: District engineer or representative, Architect/Engineer/Designer and Contractor.
- C. Record minutes and distribute copies within 5 days after meeting to participants, with two copies to District Engineer, Architect/Engineer/Designer, participants and those affected by decisions made.

1.5 SITE MOBILIZATION MEETING

- A. Architect/Engineer/Designer will schedule a meeting at the Project site prior to Contractor occupancy.
- B. Architect/Engineer/Designer will record minutes and distributes copies within 5 days after meeting to participants, with two copies to Architect/Engineer/Designer, participants and those affected by decisions made.

1.6 PROGRESS MEETINGS

- A. Schedule and administer meetings throughout progress of the Work at when arranged by Architect/Engineer/Designer.
- B. Architect/Engineer/Designer will make arrangements for meetings, prepare agenda with copies for participants, and preside at meetings.
- C. Attendance Required: Job superintendent, major Subcontractors and suppliers, District engineer representative, Architect/Engineer/Designer, as appropriate to agenda topics for each meeting.
- D. Agenda:
 - 1. Review of Work progress.
 - 2. Field observations, problems, and decisions.
 - 3. Identification of problems, which impede planned progress.
 - 4. Maintenance of progress schedule.
 - 5. Corrective measures to regain projected schedules.
 - 6. Coordination of projected progress.
 - 7. Effect of proposed changes on progress schedule and coordination.
- E. Record minutes and distributes copies within 5 days after meeting to participants and those affected by decisions made.

1.7 PREINSTALLATION MEETING

- A. When required in individual specification sections, convene a pre-installation meeting at the site prior to commencing work of the section.
- B. Notify Architect/Engineer/Designer seven days in advance of meeting date.
- C. Prepare agenda and preside at meeting:
 - 1. Review conditions of installation, preparation and installation procedures.
 - 2. Review coordination with related work.
- D. Record minutes and distributes copies within 5 days after meeting to participants and those affected by decisions made.

PART 2 PRODUCTS

Not used

PART 3 EXECUTION

3.1 CUTTING AND PATCHING

- A. Employ skilled and experienced installer to perform cutting and patching.
- B. Submit written request in advance of cutting or altering elements, which affect:
 - 1. Structural integrity of element.
 - 2. Integrity of weather-exposed or moisture-resistant elements.
 - 3. Work of Owner or separate contractor.
- C. Execute cutting, fitting, and patching to complete Work, and to:
 - 1. Uncover Work to install or correct ill-timed Work.
 - 2. Remove and replace defective and non-conforming Work.
 - 3. Provide openings in elements of Work for penetrations of mechanical and electrical Work.
- D. Cut masonry and concrete materials using masonry saw or core drill.
- E. Fit Work tight to pipes, sleeves, ducts, conduit and other penetrations through surfaces.
- F. Maintain integrity of wall, ceiling, or floor construction; completely seal voids.
- G. Refinish surfaces to match adjacent finishes. For continuous surfaces, refinish to nearest intersection; for an assembly, refinish entire unit.
- H. Identify hazardous substances or conditions exposed during the Work to the Architect/Engineer/Designer for decision or remedy.

3.2 ALTERATION PROJECT PROCEDURES

- A. Materials: As specified in Product sections; match existing Products and work for patching and extending work.
- B. Close openings in exterior surfaces to protect existing work from weather and extremes of temperature and humidity.
- C. When finished surfaces are cut so that a smooth transition with new Work is not possible, terminate existing surface along a straight line at a natural line of division and submit recommendation to Architect/Engineer/Designer for review.
- D. Patch or replace portions of existing surfaces that are damaged, lifted, discolored or showing other imperfections.
- E. Finish surfaces as specified in individual Product sections.

END OF SECTION

01300

SUBMITTAL REQUIREMENTS

PART 1 GENERAL

1.1 SECTION INCLUDES

- A. Submittal procedures.
- B. Construction progress schedules.
- C. Proposed Products list.
- D. Product Data.
- E. Shop Drawings.
- F. Samples.
- G. Design data.
- H. Test reports.
- I. Certificates.
- J. Manufacturer's instructions.
- K. Manufacturer's field reports.
- L. Erection drawings.
- M. Construction photographs.

1.2 RELATED SECTIONS

- A. Section 01300 - Submittals
- B. Section 01400 - Quality Control: Manufacturers' field services and reports.
- C. Section 01700 - Contract Closeout: Contract warranties, bonds, manufacturers' certificates and closeout submittals.

1.3 REFERENCES

- A. AGC Associated General Contractors of America publication "The Use of CPM in Construction - A Manual for General Contractors and the Construction Industry".

1.4 SUBMITTAL PROCEDURES

- A. Transmit each submittal with Architect/Engineer/Designer accepted form.
- B. Identify Project, Contractor, Subcontractor or supplier; pertinent drawing and detail number and specification section number, as appropriate.
- C. Apply Contractor's stamp, signed or initialed certifying that review, approval, verification of Products required, field dimensions, adjacent construction Work and coordination of information is in accordance with the requirements of the Work and Contract Documents.
- D. Schedule submittals to expedite the Project, and deliver to Architect/Engineer/Designer at business address. Coordinate submission of related items.
- E. For each submittal for review, allow 15 days excluding delivery time to and from the contractor.
- F. Identify variations from Contract Documents and Product or system limitations, which may be detrimental to successful performance of the completed Work.
- G. Submittals not requested will not be recognized or processed.

1.5 CONSTRUCTION PROGRESS SCHEDULES

- A. Submit initial schedule in duplicate within 15 days after date established in Notice to Proceed.
- B. Revise and resubmit as required.
- C. Submit revised schedules with each Application for Payment, identifying changes since previous version.
- D. Submit a horizontal bar chart with separate line for each major portion of Work or operation, identifying first workday of each week.

1.6 PROPOSED PRODUCTS LIST

- A. Within 15 days after date of Notice to Proceed, submit list of major products proposed for use, with name of manufacturer, trade name and model number of each product.
- B. For products specified only by reference standards, give manufacturer, trade name, model or catalog designation and reference standards.

1.7 PRODUCT DATA

- A. Product Data For Review:
 - 1. Submitted to Architect/Engineer/Designer for review for the limited purpose of checking for conformance with information given and the design concept expressed in the contract documents.
 - 2. After review, provide copies and distribute in accordance with SUBMITTAL PROCEDURES article above and for record documents purposes described in Section 01700 - CONTRACT CLOSEOUT.
- B. Product Data For Information:
 - 1. Submitted for the Architect/Engineer/Designer's knowledge as contract administrator or for the Owner.
- C. Product Data For Project Closeout:
 - 1. Submitted for the Owner's benefit during and after project completion.
- D. Submit the number of copies, which the Contractor requires, plus two copies that will be retained by the Architect/Engineer/Designer.
- E. Mark each copy to identify applicable products, models, options and other data. Supplement manufacturers' standard data to provide information specific to this Project.
- F. After review distribute in accordance with the Submittal Procedures article above and provide copies for record documents described in Section 01700 - CONTRACT CLOSEOUT.

1.8 SHOP DRAWINGS

- A. Shop Drawings For Review:
 - 1. Submitted to Architect/Engineer/Designer for review for the limited purpose of checking for conformance with information given and the design concept expressed in the contract documents.
 - 2. After review, produce copies and distribute in accordance with SUBMITTAL PROCEDURES article above and for record documents purposes described in Section 01700 - CONTRACT CLOSEOUT.
- B. Shop Drawings For Information:
 - 1. Submitted for the Architect/Engineer/Designer's knowledge as contract administrator or for the Owner.

- C. Shop Drawings For Project Closeout:
 - 1. Submitted for the Owner's benefit during and after project completion.
- D. Indicate special utility and electrical characteristics, utility connection requirements and location of utility outlets for service for functional equipment and appliances.
- E. Submit in the form of one reproducible transparency and one opaque reproduction.

1.9 SAMPLES

- A. Samples For Review:
 - 1. Submitted to Architect/Engineer/Designer for review for the limited purpose of checking for conformance with information given and the design concept expressed in the contract documents.
 - 2. After review, produce duplicates and distribute in accordance with SUBMITTAL PROCEDURES article above and for record documents purposes described in Section 01700 - CONTRACT CLOSEOUT.
- B. Samples For Information:
 - 1. Submitted for the Architect/Engineer/Designer's knowledge as contract administrator or for the Owner.
- C. Samples For Selection:
 - 1. Submitted to Architect/Engineer/Designer for aesthetic, color, or finish selection.
 - 2. Submit samples of finishes for Architect/Engineer/Designer selection.
 - 3. After review, produce duplicates and distribute in accordance with SUBMITTAL PROCEDURES article above and for record documents purposes described in Section 01700 - CONTRACT CLOSEOUT.

1.10 DESIGN DATA

- A. Submit for the Architect/Engineer/Designer's knowledge as contract administrator or for the Owner.
- B. Submit for information for the limited purpose of assessing conformance with information given and the design concept expressed in the contract documents.

1.11 TEST REPORTS

- A. Submit for the Architect/Engineer/Designer's knowledge as contract administrator or for the Owner.
- B. Submit test reports for information for the limited purpose of assessing conformance with information given and the design concept expressed in the contract documents.

1.12 CERTIFICATES

- A. When specified in individual specification sections, submit certification by the manufacturer, installation/application subcontractor, or the Contractor to Architect/Engineer/Designer, in quantities specified for Product Data.
- B. Indicate material or Product conforms to or exceeds specified requirements. Submit supporting reference data, affidavits and certifications as appropriate.
- C. Certificates may be recent or previous test results on material or Product but must be acceptable to Architect/Engineer/Designer.

1.13 MANUFACTURER'S INSTRUCTIONS

- A. When specified in individual specification sections, submit printed instructions for delivery,

storage, assembly, installation, and start-up, adjusting and finishing, to Architect/Engineer/Designer for delivery to owner in quantities specified for Product Data.

- B. Indicate special procedures, perimeter conditions requiring special attention and special environmental criteria required for application or installation.
- C. Refer to Section 01400 - Quality Control, Manufacturers' Field Services article.

1.14 MANUFACTURER'S FIELD REPORTS

- A. Submit reports for the Architect/Engineer/Designer's benefit as contract administrator or for the Owner.
- B. Submit for information for the limited purpose of assessing conformance with information given and the design concept expressed in the contract documents.

1.15 ERECTION DRAWINGS

- A. Submit drawings for the Architect/Engineer/Designer's benefit as contract administrator or for the Owner.
- B. Submit for information for the limited purpose of assessing conformance with information given and the design concept expressed in the contract documents.
- C. Data indicating inappropriate or unacceptable Work may be subject to action by the Architect/Engineer/Designer or Owner.

END OF SECTION

01400

QUALITY CONTROL REQUIREMENTS

PART 1 GENERAL

1.1 SECTION INCLUDES

- A. Quality assurance - control of installation.
- B. Tolerances
- C. References and standards.
- D. Mock-up.
- E. Inspecting and testing laboratory services.
- F. Manufacturers' field services.

1.2 RELATED SECTIONS

- A. Section 01300 - Submittals: Submission of manufacturers' instructions and certificates.
- B. Section 01600 - Material and Equipment: Requirements for material and product quality.
- C. Section 01650 - Starting of Systems.

1.3 QUALITY ASSURANCE - CONTROL OF INSTALLATION

- A. Monitor quality control over suppliers, manufacturers, Products, services, site conditions and workmanship, to produce Work of specified quality.
- B. Comply with manufacturers' instructions, including each step in sequence.
- C. Should manufacturers' instructions conflict with Contract Documents, request clarification from Architect/Engineer/Designer before proceeding.
- D. Comply with specified standards as minimum quality for the Work except where more stringent tolerances, codes or specified requirements indicate higher standards or more precise workmanship.
- E. Perform Work by persons qualified to produce required and specified quality.
- F. Verify that field measurements are as indicated on shop drawings or as instructed by the manufacturer.
- G. Secure Products in place with positive anchorage devices designed and sized to withstand stresses, vibration, physical distortion, or disfigurement.

1.4 TOLERANCES

- A. Monitor fabrication and installation tolerance control of Products to produce acceptable Work. Do not permit tolerances to accumulate.
- B. Comply with manufacturers' tolerances. Should manufacturers' tolerances conflict with Contract Documents, request clarification from Architect/Engineer/Designer before proceeding.
- C. Adjust Products to appropriate dimensions; position before securing Products in place.

1.5 REFERENCES AND STANDARDS

- A. For Products or workmanship specified by association, trade or other consensus standards, comply with requirements of the standard, except when more rigid requirements are specified or are required by applicable codes.

- B. Conform to reference standard by date of issue current on date for receiving bids or date specified in the individual specification sections, except where a specific date is established by code.
- C. Neither the contractual relationships, duties or responsibilities of the parties in Contract nor those of the Architect/Engineer/Designer shall be altered from the Contract Documents by mention or inference otherwise in any reference document.

1.6 TESTING SERVICES

- A. Contractor to provide all testing services as called out in these specifications.
- B. Testing and source quality control may occur on or off the project site. Perform off-site testing as required by the Architect/Engineer/Designer or the Owner.
- C. Testing does not relieve Contractor to perform Work to contract requirements.
- D. Re-testing required because of non-conformance to specified requirements shall be performed by the same MoDOT personnel on instructions by the Architect/Engineer/Designer.

1.7 INSPECTION SERVICES

- A. Owner will employ MoDOT Personnel to perform inspection.
- B. Inspecting may occur on or off the project site. Perform off-site inspecting as required by the Architect/Engineer/Designer or the Owner.
- C. Inspecting does not relieve Contractor to perform Work to contract requirements.

1.8 MANUFACTURERS' FIELD SERVICES

- A. When specified in individual specification sections, require material or Product suppliers or manufacturers to provide qualified staff personnel to observe site conditions, conditions of surfaces and installation, quality of workmanship, start-up of equipment, test, adjust and the balancing of equipment as applicable and to initiate instructions when necessary.
- B. Report observations and site decisions or instructions given to applicators or installers that are supplemental or contrary to manufacturers' written instructions.
- C. Refer to Section 01300 - SUBMITTALS, MANUFACTURERS' FIELD REPORTS article.

PART 2 EXECUTION

2.1 EXAMINATION

- A. Verify that existing site conditions and substrate surfaces are acceptable for subsequent Work. Beginning new Work means acceptance of existing conditions.
- B. Verify that existing substrate is capable of structural support or attachment of new Work being applied or attached.

2.2 PREPARATION

- A. Clean substrate surfaces prior to applying next material or substance.
- B. Seal cracks or openings of substrate prior to applying next material or substance.
- C. Apply manufacturer required or recommended substrate primer, sealer or conditioner prior to applying any new material or substance in contact or bond.

END OF SECTION

CONSTRUCTION FACILITIES AND TEMPORARY CONTROL REQUIREMENTS

PART 1 GENERAL

1.1 SECTION INCLUDES

- A. Temporary Utilities: Electricity, telephone service, facsimile service and sanitary facilities.
- B. Temporary Controls: enclosures and fencing, protection of the Work and water control.
- C. Construction Facilities: progress cleaning and temporary buildings.

1.2 TEMPORARY ELECTRICITY

Temporary power service furnished by MoDOT.

1.3 TEMPORARY WATER SERVICE

- A. Connect to existing water source as directed for construction operations at time of project mobilization.
- B. Contractor will reimburse Owner for water used in construction as agreed upon at time of project mobilization.

1.4 WATER CONTROL

- A. Grade site to drain. Maintain excavations free of water. Provide, operate and maintain pumping equipment.
- B. Protect site from puddling or running water. Provide water barriers as required to protect site from soil erosion.

1.5 PROTECTION OF INSTALLED WORK

- A. Protect installed Work and provide special protection where specified in individual specification sections.
- B. Provide temporary and removable protection for installed Products. Control activity in immediate work area to prevent damage.
- C. Provide protective coverings at walls, projections, jambs, sills and soffits of openings.
- D. Protect finished floors, stairs, and other surfaces from traffic, dirt, wear, damage or movement of heavy objects, by protecting with durable sheet materials.
- E. Prohibit traffic or storage upon waterproofed or roofed surfaces. If traffic or activity is necessary, obtain recommendations for protection from waterproofing or roofing material manufacturer.
- F. Prohibit traffic from landscaped areas.

1.6 SECURITY

- A. Provide security and facilities to protect Work and existing facilities and Owner's operations from unauthorized entry, vandalism or theft.
- B. Coordinate with Owner's security program.

1.7 ACCESS ROADS

- A. Provide and maintain access to fire hydrants, free of obstructions.
- B. Provide means of removing mud from vehicle wheels before entering streets.
- C. Designated existing on-site roads may be used for construction traffic.

1.8 PROGRESS CLEANING AND WASTE REMOVAL

- A. Maintain areas free of waste materials, debris and rubbish. Maintain site in a clean and orderly condition.
- B. Remove debris and rubbish from pipe chases, plenums, attics, crawl spaces and other closed or remote spaces, prior to enclosing the space.
- C. Broom and vacuum clean interior areas prior to start of surface finishing and continue cleaning to eliminate dust.
- D. Collect and remove waste materials, debris and rubbish from site periodically and dispose off-site.
- E. Open free-fall chutes are not permitted. Terminate closed chutes into appropriate containers with lids.

1.9 REMOVAL OF UTILITIES, FACILITIES, AND CONTROLS

- A. Remove temporary utilities, equipment, facilities and materials prior to Final Application for Payment inspection.
- B. Clean and repair damage caused by installation or use of temporary work.
- C. Restore existing facilities used during construction to original condition. Restore permanent facilities used during construction to specified condition.

PART 2 PRODUCTS

Not Used.

PART 3 EXECUTION

Not Used.

END OF SECTION

MATERIAL AND EQUIPMENT REQUIREMENT

PART 1 GENERAL

1.1 SECTION INCLUDES

- A. Products.
- B. Transportation and handling.
- C. Storage and protection.
- D. Product options.
- E. Substitutions.

1.2 RELATED SECTIONS

- A. Instructions to Bidders: Product options and substitution procedures.
- B. Section 01400 - Quality Control: Product quality monitoring.

1.3 PRODUCTS

- A. Do not use materials and equipment removed from existing premises, except as specifically permitted by the Contract Documents.
- B. Provide interchangeable components of the same manufacture for components being replaced.

1.4 TRANSPORTATION AND HANDLING

- A. Transport and handle Products in accordance with manufacturer's instructions.
- B. Promptly inspect shipments to ensure that Products comply with requirements, quantities are correct and products are undamaged.
- C. Provide equipment and personnel to handle Products by methods to prevent soiling, disfigurement or damage.

1.5 STORAGE AND PROTECTION

- A. Store and protect Products in accordance with manufacturers' instructions.
- B. Store with seals and labels intact and legible.
- C. Store sensitive Products in weather tight, climate controlled, enclosures in an environment favorable to Product.
- D. For exterior storage of fabricated Products, place on sloped supports above ground.
- E. Provide bonded off-site storage and protection when site does not permit on-site storage or protection.
- F. Cover Products subject to deterioration with impervious sheet covering. Provide ventilation to prevent condensation and degradation of Products.
- G. Store loose granular materials on solid flat surfaces in a well-drained area. Prevent mixing with foreign matter.
- H. Provide equipment and personnel to store Products by methods to prevent soiling, disfigurement or damage.

- I. Arrange storage of Products to permit access for inspection. Periodically inspect to verify Products are undamaged and are maintained in acceptable condition.

1.6 PRODUCT OPTIONS

- A. Products Specified by Reference Standards or by Description Only: Any Product meeting those standards or description is acceptable.
- B. Products Specified by Naming One or More Manufacturers: Products of manufacturers named and meeting specifications, no options or substitutions allowed.
- C. Products Specified by Naming One or More Manufacturers with a Provision for Substitutions: Submit a request for substitution for any manufacturer not named in accordance with the following article.

1.7 SUBSTITUTIONS

- A. Architect/Engineer/Designer will consider requests for Substitutions only within 15 days after date established in Notice to Proceed.
- B. Substitutions may be considered when a Product becomes unavailable through no fault of the Contractor.
- C. Document each request with complete data substantiating compliance of proposed Substitution with Contract Documents.
- D. A request constitutes a representation that the Contractor:
 - 1. Has investigated proposed Product and determined that it meets or exceeds the quality level of the specified Product.
 - 2. Will provide the same warranty for the Substitution as for the specified Product.
 - 3. Will coordinate installation and make changes to other Work that may be required for the Work to be complete with no additional cost to Owner.
 - 4. Waives claims for additional costs or time extension that may subsequently become apparent.
 - 5. Will reimburse Owner for review or redesign services associated with re-approval by authorities.
- E. Substitutions will not be considered when they are indicated or implied on shop drawing or product data submittals, without separate written request or when acceptance will require revision to the Contract Documents.
- F. Substitution Submittal Procedure:
 - 1. Submit three copies of request for Substitution for consideration. Limit each request to one proposed Substitution.
 - 2. Submit shop drawings, product data and certified test results attesting to the proposed Product equivalence. Burden of proof is on proposer.
 - 3. The Architect/Engineer/Designer will notify Contractor in writing of decision to accept or reject request.

PART 2 PRODUCTS

Not Used.

PART 3 EXECUTION

Not Used.

END OF SECTION

CONTRACT CLOSEOUT REQUIREMENT

PART 1 GENERAL

1.1 SECTION INCLUDES

- A. Closeout procedures.
- B. Final cleaning.
- C. Adjusting.
- D. Project record documents.
- E. Operation and maintenance data.
- F. Spare parts and maintenance Products.
- G. Warranties.

1.2 RELATED SECTIONS

- A. Section 01500 - Construction Facilities and Temporary Controls: Progress cleaning.
- B. Section 01650 - Starting of Systems: System start-up, testing, adjusting and balancing.

1.3 CLOSEOUT PROCEDURES

- A. Submit written certification that Contract Documents have been reviewed, Work has been inspected, and that Work is complete in accordance with Contract Documents and ready for Architect/Engineer/Designer's review.
- B. Provide submittals to Owner that is required by governing or other authorities.
- C. Submit final Application for Payment identifying total adjusted Contract Sum, previous payments and sum remaining due.
- D. Owner will occupy portions of the building as specified in Section 01010.
- E. Projects shall not be accepted by MoDOT until the vendor has completed all punch list items. The vendor will then have 30 days to submit all required paperwork necessary to close the project. Failure to submit the required paperwork within 30 days could result in the debarment or suspension of the contractor from future projects.

1.4 FINAL CLEANING

- A. Execute final cleaning prior to final project assessment. Clean interior and exterior glass, surfaces exposed to view; remove temporary labels, stains and foreign substances, polish transparent and glossy surfaces, vacuum carpeted and soft surfaces.
- B. Clean equipment and fixtures to a sanitary condition with cleaning materials appropriate to the surface and material being cleaned.
- C. Clean or replace filters of operating equipment used during construction and/or adjustment.
- D. Clean debris from roofs, gutters, downspouts and drainage systems.
- E. Clean site; sweep paved areas, rake clean landscaped surfaces.
- F. Remove waste and surplus materials, rubbish and construction facilities from the site.

1.5 ADJUSTING

- A. Adjust operating Products and equipment to ensure smooth and unhindered operation.

1.6 PROJECT RECORD DOCUMENTS

- A. Store record documents separate from documents used for construction.
- B. Record information concurrent with construction progress.
- C. Specifications: Legibly mark and record at each Product section description of actual Products installed, including the following:
 - 1. Manufacturer's name and product model and number.
 - 2. Product substitutions or alternates utilized.
 - 3. Changes made by Addenda and modifications.
- D. Record Drawings and Shop Drawings: Legibly mark each item to record actual construction including:
 - 1. Measured depths of foundations in relation to finish main floor datum.
 - 2. Measured horizontal and vertical locations of underground utilities and appurtenances, referenced to permanent surface improvements.
 - 3. Measured locations of internal utilities and appurtenances concealed in construction, referenced to visible and accessible features of the Work.
 - 4. Field changes of dimension and detail.
 - 5. Details not on original Contract drawings.
- E. Submit documents to Architect/Engineer/Designer's with claim for final Application for Payment.

1.7 OPERATION AND MAINTENANCE DATA

- A. Submit data bound in 8-1/2 x 11 inch (A4) text pages, three D side ring binders with durable plastic covers.
- B. Prepare binder cover with printed title "OPERATION AND MAINTENANCE INSTRUCTIONS", title of project and subject matter of binder when multiple binders are required.
- C. Internally subdivide the binder contents with permanent page dividers, logically organized; with tab titling clearly printed under reinforced laminated plastic tabs.
- D. Submit 1 draft copy of completed volumes 15 days prior to final inspection. This copy will be reviewed and returned with Architect/Engineer/Designer comments. Revise content of all document sets as required prior to final submission.
- E. Submit two sets of revised final volumes, within 10 days after final inspection.

1.8 SPARE PARTS AND MAINTENANCE PRODUCTS

- A. Provide spare parts, maintenance, and extra Products in quantities specified individual specification sections.
- B. Deliver to Project site; obtain receipt prior to final payment.
- C. Examine system components at a frequency consistent with reliable operation. Clean, adjust and lubricate as required.
- D. Include systematic examination, adjustment, and lubrication of components. Repair or replace parts whenever required. Use parts produced by the manufacturer of the original component.
- E. Maintenance service shall not be assigned or transferred to any agent or Subcontractor without prior written consent of the Owner.

1.9 WARRANTIES

- A. Execute and assemble transferable warranty documents from Subcontractors, suppliers and manufacturers.
- B. Submit prior to final Application for Payment.
- C. For items of Work delayed beyond date of Final Completion, provide updated submittal within 10 days after acceptance, listing date of acceptance as start of the warranty period.

PART 2 PRODUCTS

Not Used.

PART 3 EXECUTION

Not Used.

JOB SPECIAL PROVISIONS TABLE OF CONTENTS

(Job Special provisions shall prevail over General Special provisions whenever in conflict therewith)

- A. UTILITY SERVICE CONNECTIONS
- B. UTILITIES
- C. GRADING SITE EROSION AND SILTATION CONTROL
- D. MoDOT STANDARDS
- E. CLEARING AND GRUBBING
- F. SITE COMPACTION
- G. SUBSURFACE BORING LOGS

	<p align="center">MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION 105 W. CAPITOL AVE. JEFFERSON CITY, MO 65102 Phone 1-888-275-6636</p>
	<p>JOB NUMBER: CLAY COUNTY, MO DATE PREPARED: 04/13/2012</p>
<p>Date:</p>	<p>ADDENDUM DATE:</p>
<p>Only the following items of the Job Special Provisions (Roadway) are authenticated by this seal:</p>	

A. UTILITY SERVICE CONNECTIONS

The contractor's first order of work will be to establish the utility connections to the parcel. Service connections shall meet the applicable State and City building codes. The contractor will be required to establish service connections for the following utilities:

GAS: The contractor will be required to stub-in a 2-inch service line from the main to the Maintenance building. Mo. Gas Energy will provide and set meter, to schedule the meter set call MGE at 816-756-5252. Allow a minimum of 5 days to set meter.

SEWER: The contractor will be required to stub-in a 6-inch line from the 12-inch sewer main to terminate near the Oil / Grease Interceptor location. The Oil / Grease Interceptor is not part of this contract. The Sewer main is a 12-inch diameter-line. When complete the connection will be inspected by Kansas City Water Sewer District's Line Maintenance Division. To schedule an inspection call KCMO WSD at 816-513-8000.

POWER: Provide 2 - 30-foot service poles with #2 AWG ground. Placement shall be in the Northeast corner of the property and in the N. Skiles Ave right-of-way. Provide single-phase, 3 wire connections between transformer and temporary distribution panel. Work shall include all conduit, wire, access boxes, connectors and circuit breakers necessary to complete the utility connection.

WATER: The contractor will be required to stub-in a 2-inch service line from the main to near the northeast corner of the Maintenance building. The contractor will be required to use copper water lines anywhere the water lines are in contact with the ground, once water line is 6 inches above the ground line the contractor may switch to another approved material for the line.

FIRE LINE: Provide a 6-inch fire service line from the main to the Fire Hydrant located on the easterly property as shown on the plans. Work shall include water line, fire hydrant and all conduit, pipe, fittings and connections necessary to complete the utility connection. The fire hydrant shall be a Clow Valve Co. 5 ¼-inches Medallion F2545 Hydrant or an approved hydrant meeting the City of Kansas City, MO. Fire department specifications.

PHONE / DATA: The contractor will be required to stub-in two 4-inch PVC conduits, equipped with a pull string, from the main trunk at North Skiles Avenue to near Maintenance building. All bends in this conduit will need to be sweeps with a minimum 3-foot radius.

The City of Kansas City will require the following permits to establish utility connections:

- A. Authorize to connect, Mr. Dion Walton 816-513-2604
- B. Water Inspection permits, Form WS14, Ms. Carla Haskins, 816-513-2133
- C. Plumbing permit
- D. Excavation permits for working in City RW (Skiles Ave)
- E. Traffic Closure permit when temporarily closing Skiles Ave.
- F. Driveway Permit, Mr. David Panek, 816-513-2562

Payment will be considered as covered by and made under the various items in the project.

B. UTILITIES

1.0 For informational purposes only the following is a list of names, addresses, and telephone numbers of the known utility companies in the area of the construction work for this improvement:

<u>Utility Company</u>	<u>Known Required Adjustment</u>
Mr. Kirk Thaelke LightCore, a CenturyLink Company 1151 CenturyTel Drive Bldg A Wentzville, MO 63385 (636) 887-4752	No
<i>Mr. Reza Zonnooz</i> City of Kansas City Water Services Dept. 4800 E. 63 rd Street Kansas City, Mo. 64130 (816) 513-0309 (Reza)	No
Mr. Jerry Woodall Level 3 Communications 1212 E. 19 th Street Kansas City, Mo. 64108 (913) 645-5032	No
Mr. Donnie Richards Missouri Gas Energy 7500 E. 35 th Street Kansas City, MO 64129 (816) 472-3464 (Donnie Richards)	No
Mr. Mark Frank AT&T 215 N. Spring Independence, MO 64050-2822 (816) 325-5614 (Mark)	No

1.1 The existence and approximate location of utility facilities known to exist, as shown on the plans, are based upon the best information available to the Commission at this time. This information is provided by the Commission "as-is" and the Commission expressly disclaims any representation or warranty as to the completeness, accuracy, or suitability of the information for

any use. Reliance upon this information is done at the risk and peril of the user, and the Commission shall not be liable for any damages that may arise from any error in the information. It is, therefore, the responsibility of the contractor to verify the above listing information indicating existence, location and status of any facility. Such verification includes direct contact with the listed utilities.

1.2 The contractor agrees that any effects of the presence of the utilities, their relocation, contractor's coordination of work with the utilities and any delay in utility relocation shall not be compensable as a suspension of work, extra work, a change in the work, as a differing site condition or otherwise including but, without limitation, delay, impact, incidental or consequential damages. The contractor's sole remedy for the effects of the presence of utilities, delay in their relocation or any other effects shall be an excusable delay as provided in Section 105.7.3. The contractor waives, for itself, its subcontractors and suppliers the compensability of the presence of utilities, delay in their relocation and any cost to the contractor, its subcontractors and suppliers in any claim or action arising out of or in relation to the work under the contract.

1.3 The contractor shall be solely responsible and liable for incidental and consequential damage to any utility facilities or interruption of the service caused by it or its subcontractors operation. The contractor shall hold and save harmless the Commission from damages to any utility facilities interruption of service by it or its subcontractor's operation.

2.0 It shall be noted by the contractor that MoDOT is a member of Missouri One Call (800 Dig Rite). Some work on this project may be in the vicinity of MoDOT utility facilities, which includes but is not limited to traffic signal cables, highway lighting circuits, ITS cables, cathodic protection cables, etc. Prior to beginning work, the contractor shall request locates from Missouri One Call. The contractor shall also complete the Notice of Intent to Perform Work form located at the Missouri Department of Transportation website:

<http://www.modot.mo.gov/asp/intentToWork.shtml>

The contractor shall submit the form over the web (preferred method) or by fax to the numbers on the printed form. The notice must be submitted a minimum of 2 and a maximum of 10 working days prior to excavation just as Missouri One Call requires.

C. GRADING SITE EROSION AND SILTATION CONTROL

Appropriate erosion and siltation controls must be used and maintained in effective operating condition during the grading project.

All exposed soil and disturbed areas shall be stabilized at the earliest practicable date.

Erosion control shall be in accordance with Section 800 of the Standard Specifications, and Missouri Standard Plans for Highway Construction Standard Drawing 806.10.

Payment will be considered as covered by and made under the various items in the project.

D. MoDOT STANDARDS

Items associated with the grading and site work are governed by Missouri Standards for Highway Construction. The document is available on the Missouri Department of Transportation web page at www.modot.mo.gov under "Business With MoDOT" "Standards and Specifications". The effective version shall be determined by the letting date of the project.

General Provisions & Supplemental Specifications

Supplemental Plans to 2011 Missouri Std. Plans
For Highway Construction

These supplemental bidding documents contain all current revisions to the bound printed versions and have important legal consequences. It shall be conclusively presumed that they are in the bidder's possession, and they have been reviewed and used by the bidder in the preparation of any bid submitted on this project.

E. CLEARING AND GRUBBING

Clearing and Grubbing shall be in accordance with Section 201 of the Standard Specifications. Payment will be considered as covered by and made under the various items in the project.

F. SITE COMPACTION

Site Compaction shall be in accordance with Section 203 of the Standard Specifications. The site shall be compacted using a tamping-type roller as outlined in Sec 203.6.

Payment will be considered as covered by and made under the various items in the project.

G. SUBSURFACE BORING LOGS


The subsurface boring logs are attached and made a part of this contract. This information was acquired to identify the various types of earth materials and estimate quantities at specific locations. The scope of this exploration did not include the determination of actual subsurface conditions or appropriate construction methods. Global stability, settlement analysis, and allowable bearing pressures were not assessed for any type of load condition. Ground water observations are not routinely recorded in all of the boring records and absence of this data does not mean that ground water will not be encountered. Any assumption anyone may make using this information will be done at their own risk.

J:/francd1/buildings_and_grounds/Liberty-Chouteau/PSE Documents Buildings/3800Skiles JSP GRADING ONLY.doc

JOB SPECIAL PROVISIONS TABLE OF CONTENTS

(Job Special provisions shall prevail over General Special provisions whenever in conflict therewith)

- A. UTILITY SERVICE CONNECTIONS
- B. UTILITIES
- C. GRADING SITE EROSION AND SILTATION CONTROL
- D. MoDOT STANDARDS
- E. CLEARING AND GRUBBING
- F. SITE COMPACTION
- G. SUBSURFACE BORING LOGS

	MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION 105 W. CAPITOL AVE. JEFFERSON CITY, MO 65102 Phone 1-888-275-6636
	JOB NUMBER: CLAY COUNTY, MO DATE PREPARED: 04/13/2012
Date:	ADDENDUM DATE:
Only the following items of the Job Special Provisions (Roadway) are authenticated by this seal:	

A. UTILITY SERVICE CONNECTIONS

The contractor's first order of work will be to establish the utility connections to the parcel.

Service connections shall meet the applicable State and City building codes. The contractor will be required to establish service connections for the following utilities:

GAS: The contractor will be required to stub-in a 2-inch service line from the main to the Maintenance building. Mo. Gas Energy will provide and set meter, to schedule the meter set call MGE at 816-756-5252. Allow a minimum of 5 days to set meter.

SEWER: The contractor will be required to stub-in a 6-inch line from the 12-inch sewer main to terminate near the Oil / Grease Interceptor location. The Oil / Grease Interceptor is not part of this contract. The Sewer main is a 12-inch diameter-line. When complete the connection will be inspected by Kansas City Water Sewer District's Line Maintenance Division. To schedule an inspection call KCMO WSD at 816-513-8000.

POWER: Provide 2 - 30-foot service poles with #2 AWG ground. Placement shall be in the Northeast corner of the property and in the N. Skiles Ave right-of-way. Provide single-phase, 3 wire connections between transformer and temporary distribution panel. Work shall include all conduit, wire, access boxes, connectors and circuit breakers necessary to complete the utility connection.

WATER: The contractor will be required to stub-in a 2-inch service line from the main to near the northeast corner of the Maintenance building. The contractor will be required to use copper water lines anywhere the water lines are in contact with the ground, once water line is 6 inches above the ground line the contractor may switch to another approved material for the line.

FIRE LINE: Provide a 6-inch fire service line from the main to the Fire Hydrant located on the easterly property as shown on the plans. Work shall include water line, fire hydrant and all conduit, pipe, fittings and connections necessary to complete the utility connection. The fire hydrant shall be a Clow Valve Co. 5 1/4-inches Medallion F2545 Hydrant or an approved hydrant meeting the City of Kansas City, MO. Fire department specifications.

PHONE / DATA: The contractor will be required to stub-in two 4-inch PVC conduits, equipped with a pull string, from the main trunk at North Skiles Avenue to near Maintenance building. All bends in this conduit will need to be sweeps with a minimum 3-foot radius.

The City of Kansas City will require the following permits to establish utility connections:

- A. Authorize to connect, Mr. Dion Walton 816-513-2604
- B. Water Inspection permits, Form WS14, Ms. Carla Haskins, 816-513-2133
- C. Plumbing permit
- D. Excavation permits for working in City R/W (Skiles Ave)
- E. Traffic Closure permit when temporarily closing Skiles Ave.
- F. Driveway Permit, Mr. David Panek, 816-513-2562

Payment will be considered as covered by and made under the various items in the project.

B. UTILITIES

1.0 For informational purposes only the following is a list of names, addresses, and telephone numbers of the known utility companies in the area of the construction work for this improvement:

<u>Utility Company</u>	<u>Known Required Adjustment</u>
Mr. Kirk Thoelke LightCore, a CenturyLink Company 1151 CenturyTel Drive Bldg A Wentzville, MO 63385 (636) 887-4752	No
Mr. Reza Zonnooz City of Kansas City Water Services Dept. 4800 E. 63 rd Street Kansas City, Mo. 64130 (816) 513-0309 (Reza)	No
Mr. Jerry Woodall Level 3 Communications 1212 E. 19 th Street Kansas City, Mo. 64108 (913) 645-5032	No
Mr. Donnie Richards Missouri Gas Energy 7500 E. 35 th Street Kansas City, MO 64129 (816) 472-3464 (Donnie Richards)	No
Mr. Mark Frank AT&T 215 N. Spring Independence, MO 64050-2822 (816) 325-5614 (Mark)	No

1.1 The existence and approximate location of utility facilities known to exist, as shown on the plans, are based upon the best information available to the Commission at this time. This information is provided by the Commission "as-is" and the Commission expressly disclaims any representation or warranty as to the completeness, accuracy, or suitability of the information for any use. Reliance upon this information is done at the risk and peril of the user, and the Commission shall not be liable for any damages that may arise from any error in the information. It is, therefore, the responsibility of the contractor to verify the above listing information indicating existence, location and status of any facility. Such verification includes direct contact with the listed utilities.

1.2 The contractor agrees that any effects of the presence of the utilities, their relocation, contractor's coordination of work with the utilities and any delay in utility relocation shall not be compensable as a suspension of work, extra work, a change in the work, as a differing site condition or otherwise including but, without limitation, delay, impact, incidental or consequential damages. The contractor's sole remedy for the effects of the presence of utilities, delay in their relocation or any other effects shall be an excusable delay as provided in Section 105.7.3. The contractor waives, for itself, its subcontractors and suppliers the compensability of the presence of utilities, delay in their relocation and any cost to the contractor, it's subcontractors and suppliers in any claim or action arising out of or in relation to the work under the contract.

1.3 The contractor shall be solely responsible and liable for incidental and consequential damage to any utility facilities or interruption of the service caused by it or its subcontractors operation. The contractor shall hold and save harmless the Commission from damages to any utility facilities interruption of service by it or its subcontractor's operation.

2.0 It shall be noted by the contractor that MoDOT is a member of Missouri One Call (800 Dig Rite). Some work on this project may be in the vicinity of MoDOT utility facilities, which includes but is not limited to traffic signal cables, highway lighting circuits, ITS cables, cathodic protection cables, etc. Prior to beginning work, the contractor shall request locates from Missouri One Call. The contractor shall also complete the Notice of Intent to Perform Work form located at the Missouri Department of Transportation website:

<http://www.modot.mo.gov/asp/intentToWork.shtml>

The contractor shall submit the form over the web (preferred method) or by fax to the numbers on the printed form. The notice must be submitted a minimum of 2 and a maximum of 10 working days prior to excavation just as Missouri One Call requires.

C. GRADING SITE EROSION AND SILTATION CONTROL

Appropriate erosion and siltation controls must be used and maintained in effective operating condition during the grading project.

All exposed soil and disturbed areas shall be stabilized at the earliest practicable date.

Erosion control shall be in accordance with Section 800 of the Standard Specifications, and Missouri Standard Plans for Highway Construction Standard Drawing 806.10.

Payment will be considered as covered by and made under the various items in the project.

D. MoDOT STANDARDS

Items associated with the grading and site work are governed by Missouri Standards for Highway Construction. The document is available on the Missouri Department of Transportation web page at www.modot.mo.gov under "Business With MoDOT" "Standards and Specifications". The effective version shall be determined by the letting date of the project.

General Provisions & Supplemental Specifications

Supplemental Plans to 2011 Missouri Std. Plans
For Highway Construction

These supplemental bidding documents contain all current revisions to the bound printed versions and have important legal consequences. It shall be conclusively presumed that they are in the bidder's possession, and they have been reviewed and used by the bidder in the preparation of any bid submitted on this project.

E. CLEARING AND GRUBBING

Clearing and Grubbing shall be in accordance with Section 201 of the Standard Specifications. Payment will be considered as covered by and made under the various items in the project.

F. SITE COMPACTION

Site Compaction shall be in accordance with Section 203 of the Standard Specifications. The site shall be compacted using a tamping-type roller as outlined in Sec 203.6.

Payment will be considered as covered by and made under the various items in the project.

G. SUBSURFACE BORING LOGS

The subsurface boring logs are attached and made a part of this contract. This information was acquired to identify the various types of earth materials and estimate quantities at specific locations. The scope of this exploration did not include the determination of actual subsurface conditions or appropriate construction methods. Global stability, settlement analysis, and allowable bearing pressures were not assessed for any type of load condition. Ground water observations are not routinely recorded in all of the boring records and absence of this data does not mean that ground water will not be encountered. Any assumption anyone may make using this information will be done at their own risk.

**Missouri Department of Transportation
Construction and Materials
Boring Data**

Job No.: R35G - Skiles County: Clay Route: _____
 Design: n/a Skew: _____ Location: near I-435
 Bent: _____ Logged By: Steve Owens Operator: Michael Donahoe
 Station: _____ Northing: _____ Date of Work: _____
 Offset: _____ Easting: _____ Depth to Water: _____
 Elevation: _____ Requested Northing: _____ Depth Hole Open: _____
 Requested Station: _____ Requested Easting: _____ Time Change: _____
 Requested Offset: _____ Equipment: CME 850
 Requested Elevation: _____ Location Note: Old 38th St. over Norfolk-Western RR bridge east approach

Depth (ft)	Graphic	Description	Elevation (ft)
0		0-25' Brown, LEAN CLAY, very stiff, moist	
10			
20			
		Bottom of borehole at 25.0 feet.	

Job No.: R35G - Skiles County: Clay Route: _____
 Design: n/a Skew: _____ Location: near I-435
 Bent: _____ Logged By: Steve Owens Operator: Michael Donahoe
 Station: _____ Northing: _____ Date of Work: _____
 Offset: _____ Easting: _____ Depth to Water: _____
 Elevation: _____ Requested Northing: _____ Depth Hole Open: _____
 Requested Station: _____ Requested Easting: _____ Time Change: _____
 Requested Offset: _____ Equipment: CME 850
 Requested Elevation: _____ Location Note: Old 38th St. over Norfolk-Western RR bridge east approach

Depth (ft)	Graphic	Description	Elevation (ft)
0		0-25' Brown, LEAN CLAY, very stiff, moist	
10			
20			
		Bottom of borehole at 25.0 feet.	

Coordinate System: Modified U.S. State Plane 1983 Coordinate Zone: Missouri Central Coordinate Proj. Factor: _____
 Coordinate Datum: NAD 83 (CONUS) Coordinate Units: U.S. Survey Feet

* Persons using this information are cautioned that the materials shown are determined by the equipment noted and accuracy of the "log of materials" is limited thereby and by judgment of the operator. THIS INFORMATION IS FOR DESIGN PURPOSES ONLY.

Missouri Department of Transportation
Construction and Materials

BORING NO. A-12-13
Page 1 of 2

Job No.: R35G - Skiles
Design: n/a
Bent: _____
Station: _____
Offset: _____
Elevation: 860.6
Requested Station: _____
Requested Offset: _____
Requested Elevation: _____
Drill No.: G-7887

County: Clay
Skew: _____
Logged By: George Davis
Northing: 1091238.7
Easting: 2793012.9
Requested Northing: _____
Requested Easting: _____
Equipment: Falling 1500 Split-Spoon Sampler, Shelby Tube
Location Note: Northeast Corner Planned Maintenance Main Bldg.
Hammer Efficiency: 80%

Route: _____
Location: near I-435
Operator: Michael Donahoe
Date of Work: 02/26/12-02/26/12
Depth to Water: _____
Depth Hole Open: 9
Time Change: 17 hours
Drilling Method: Mud Rotary

Depth (ft)	Graphic	Description	Elevation (ft)	Sample Type	REC % (ROD %)	Blow Counts (N ₆₀)	Shear Strength Data	Field Tests	Index Tests
0		0-12.9' Brown, LEAN CLAY, very hard, moist	860						
5			855					PP > 0.00 tsf Torvane > 0.90 tsf	LL = 31 PL = 16 MC = 17.1%
10			850	X	100	5-10-13 (31)		PP > 4.50 tsf	MC = 15.0%
15		12.9-14.7' Gray, LEAN CLAY, hard, moist		X	100	6-8-7 (20)		PP > 4.50 tsf Torvane > 0.90 tsf	LL = 29 PL = 18 MC = 19.1%
17.3		14.7-17.3' Brown, LEAN CLAY, very soft, moist	845					PP = 4.00 tsf	MC = 20.7%
20		17.3-22.5' Brown, LEAN CLAY, stiff, moist	840		100	2-5-6 (15)		PP < 0.25 tsf Torvane < 0.10 tsf	LL = 26 PL = 20 MC = 17.9%
25		22.5-37.5' Light gray, LEAN CLAY, very stiff to soft, moist	835		100	3-4-6 (13)		PP = 1.00 tsf	MC = 19.9%
30			830		100	4-2-3 (7)		PP = 1.30 tsf Torvane = 0.40 tsf	LL = 36 PL = 17 MC = 24.4%
35						4-7-6 (17)		PP = 1.40 tsf Torvane = 0.40 tsf	MC = 21.3%
								PP = 1.40 tsf Torvane = 0.40 tsf	MC = 22.6%
								PP = 0.25 tsf	MC = 24.5%
								PP = 1.00 tsf	

LETTER BOREHOLE - MODOT_07-28-11.GDT - 4/10/12 13:02 - J:\SG\INT\PROJECT FILES\R35G - SKILES.GPJ

N₆₀ = (Em/60)N_m N₆₀ - Corrected N value for standard 60% SPT efficiency; Em - Measured hammer efficiency in percent; N_m - Observed N-value
(1) = Assumed, (2) = Actual
Coordinate System: Modified U.S. State Plane 1983 Coordinate Zone: Missouri Central Coordinate Proj. Factor: _____
Coordinate Datum: NAD 83 (CONUS) Coordinate Units: U.S. Survey Feet

* Persons using this information are cautioned that the materials shown are determined by the equipment noted and accuracy of the "log of materials" is limited thereby and by judgement of the operator. THIS INFORMATION IS FOR DESIGN PURPOSES ONLY.

Missouri Department of Transportation
Construction and Materials

BORING NO. A-12-13
Page 2 of 2

Job No.: R35G - Skiles County: Clay Route: _____
 Design: n/a Skew: _____ Location: near I-435
 Bent: _____ Logged By: George Davis Operator: Michael Donahoe
 Station: _____ Northing: 1091238.7 Date of Work: 02/26/12-02/26/12
 Offset: _____ Easting: 2793012.9 Depth to Water: _____
 Elevation: 860.6 Requested Northing: _____ Depth Hole Open: 9
 Requested Station: _____ Requested Easting: _____ Time Change: 17 hours
 Requested Offset: _____ Equipment: Falling 1500, Split-Spoon Sampler, Shelby Tube
 Requested Elevation: _____ Location Note: Northeast Corner Planned Maintenance Main Bldg.
 Drill No.: G-7887 Hammer Efficiency: 80% Drilling Method: Mud Rotary

Depth (ft)	Graphic	Description	Elevation (ft)	Sample Type	REC % (ROD %)	Blow Counts (N ₆₀)	Shear Strength Data	Field Tests	Index Tests
36		22.5-37.5' Light gray, LEAN CLAY, very stiff to soft, moist (continued)	825	X		3-5-8 (17)		PP = 2.76 lsf	
40		37.5-41.5' Yellowish brown, FAT CLAY, very stiff, moist, shaly,	820	X		17-29-38 (89)			
		Bottom of borehole at 41.5 feet.							

LETTER BOREHOLE - MODOT_07-29-11.GDT - 4/10/12 12:02 - J:\SIG\INT\PROJECT FILES\R35G - SKILES.GPJ

N₆₀ = (Em/60)Nm N₆₀ - Corrected N value for standard 60% SPT efficiency; Em - Measured hammer efficiency in percent; Nm - Observed N-value
 (1) = Assumed, (2) = Actual

Coordinate System: Modified U.S. State Plane 1983 Coordinate Zone: Missouri Central Coordinate Proj. Factor: _____

Coordinate Datum: NAD 83 (CONUS) Coordinate Units: U.S. Survey Feet

* Persons using this information are cautioned that the materials shown are determined by the equipment noted and accuracy of the "log of materials" is limited thereby and by judgement of the operator. THIS INFORMATION IS FOR DESIGN PURPOSES ONLY.

Missouri Department of Transportation
Construction and Materials

BORING NO. A-12-14
Page 1 of 2

Job No.: R35G - Skiles
 Design: n/a
 Bent: _____
 Station: _____
 Offset: _____
 Elevation: 860.4
 Requested Station: _____
 Requested Offset: _____
 Requested Elevation: _____
 Drill No.: G-7887

County: Clay
 Skew: _____
 Logged By: George Davis
 Northing: 109288.7
 Easting: 2793012.9
 Requested Northing: _____
 Requested Easting: _____
 Equipment: Falling 1500 Split-Spoon Sampler, Shelby Tube
 Location Note: Southeast Corner Planned Maintenance Main Bldg.
 Hammer Efficiency: 80%

Route: _____
 Location: near I-435
 Operator: Michael Donahoe
 Date of Work: 02/27/12-02/27/12
 Depth to Water: _____
 Depth Hole Open: _____
 Time Change: _____
 Drilling Method: Mud Rotary

Depth (ft)	Graphic	Description	Elevation (ft)	Sample Type	REC % (ROD %)	Blow Counts (N ₆₀)	Shear Strength Data	Field Tests	Index Tests
0		0-15' Brown, LEAN CLAY, very hard, moist	860						
5			855				Qu Test Results UCS = 3.52 ksf MC = 17.7% γ _{moist} = 120.3 pcf	PP = 7.00 tsf Torvane >0.90 tsf	MC = 16.6%
10			850	X	100	7-11-13 (32)		PP = 6.60 tsf	LL = 29 PL = 18 MC = 17.8%
15			845	X	93	3-7-8 (20)		PP = 5.00 tsf Torvane >0.90 tsf	MC = 25.2%
20		15-22.3' Dark brown, LEAN CLAY, soft to medium stiff, moist	840	X	80	2-4-7 (16)	Qu Test Results UCS = 0.388 ksf MC = 30.3% γ _{moist} = 114.4 pcf	PP = 8.20 tsf	LL = 29 PL = 18 MC = 16.5%
25			835	X	100	1-1-1 (3)		PP = 0.75 tsf Torvane <0.10 tsf	MC = 63.6%
30		22.3-30' Gray, LEAN CLAY, very soft, moist	830	X	100	1-1-1 (3)		PP = 0.40 tsf Torvane = 0.27 tsf	LL = 39 PL = 18 MC = 22.1%
35		30-35' Gray, LEAN CLAY scattered gravel, stiff, moist		X	87	4-5-7 (16)	Qu Test Results UCS = 2.24 ksf MC = 21.8% γ _{moist} = 130.4 pcf	PP <0.25 tsf	MC = 29.8%
				X				PP <0.25 tsf Torvane = 0.20 tsf	LL = 30 PL = 19 MC = 29.8%
				X				PP <0.25 tsf	MC = 33.8%
				X				PP = 1.25 tsf Torvane = 0.60 tsf	LL = 28 PL = 18 MC = 22.3%
				X				PP = 1.75 tsf	MC = 20.3%

N₆₀ = (Em/60)Nm N₆₀ - Corrected N value for standard 60% SPT efficiency; Em - Measured hammer efficiency in percent; Nm - Observed N-value
 (1) = Assumed, (2) = Actual

Coordinate System: Modified U.S. State Plane 1983 Coordinate Zone: Missouri Central Coordinate Proj. Factor: _____
 Coordinate Datum: NAD 83 (CONUS) Coordinate Units: U.S. Survey Feet

* Persons using this information are cautioned that the materials shown are determined by the equipment noted and accuracy of the "log of materials" is limited thereby and by judgement of the operator. THIS INFORMATION IS FOR DESIGN PURPOSES ONLY.

LETTER BOREHOLE - MODDOT_07-29-11.GDT - 4/10/12 13:02 - J:\SIGINT\PROJECT FILES\R35G - SKILES.GPJ

Missouri Department of Transportation
Construction and Materials

BORING NO. A-12-14
Page 2 of 2

Job No.: R35G - Skiles County: Clay Route: _____
 Design: n/a Skew: _____ Location: near I-435
 Bent: _____ Logged By: George Davis Operator: Michael Donahoe
 Station: _____ Northing: 109288.7 Date of Work: 02/27/12-02/27/12
 Offset: _____ Easting: 2793012.9 Depth to Water: _____
 Elevation: 860.4 Requested Northing: _____ Depth Hole Open: _____
 Requested Station: _____ Requested Easting: _____ Time Change: _____
 Requested Offset: _____ Equipment: Falling 1500 Split-Spoon Sampler, Shelby Tube
 Requested Elevation: _____ Location Note: Southeast Corner Planned Maintenance Main Bldg.
 Drill No.: G-7887 Hammer Efficiency: 80% Drilling Method: Mud Rotary

Depth (ft)	Graphic	Description	Elevation (ft)	Sample Type	REC % (ROD %)	Blow Counts (N ₆₀)	Shear Strength Data	Field Tests	Index Tests
35			825					PP = 3.00 tsf	
		35-43.5' Clay Shale, grayish brown to gray, thinly laminated, soft, slightly weathered to highly weathered, micaceous		X		31-38/0.3'		PP = 6.40 tsf	
40			820						
		Bottom of borehole at 43.5 feet.							

LETTER BOREHOLE - MODDOT_07-28-11_60T - 4/10/12 13:02 - J:\SIG\INT\PROJECT FILES\R35G - SKILES.GPJ

N₆₀ = (Em/60)Nm N₆₀ - Corrected N value for standard 60% SPT efficiency; Em - Measured hammer efficiency in percent; Nm - Observed N-value
 (1) = Assumed, (2) = Actual

Coordinate System: Modified U.S. State Plane 1983 Coordinate Zone: Missouri Central Coordinate Proj. Factor: _____

Coordinate Datum: NAD 83 (CONUS) Coordinate Units: U.S. Survey Feet

* Persons using this information are cautioned that the materials shown are determined by the equipment noted and accuracy of the "log of materials" is limited thereby and by judgement of the operator. THIS INFORMATION IS FOR DESIGN PURPOSES ONLY.

Missouri Department of Transportation
Construction and Materials

BORING NO. A-12-15
Page 1 of 2

Job No.: R35G - Skiles
Design: n/a
Bent: _____
Station: _____
Offset: _____
Elevation: 855.9
Requested Station: _____
Requested Offset: _____
Requested Elevation: _____
Drill No.: G-7887

County: Clay
Skew: _____
Logged By: George Davis
Northing: 1090951.5
Easting: 2792846.9
Requested Northing: _____
Requested Easting: _____
Equipment: Falling 1500 Split-Spoon Sampler, Shelby Tube
Location Note: Southeast Corner Planned Salt/ Brine Storage Bldg.
Hammer Efficiency: 80%

Route: _____
Location: near I-435
Operator: Michael Donahoe
Date of Work: 02/29/12-02/29/12
Depth to Water: _____
Depth Hole Open: _____
Time Change: _____
Drilling Method: Mud Rotary

Depth (ft)	Graphic	Description	Elevation (ft)	Sample Type	REC % (RQD %)	Blow Counts (N ₆₀)	Shear Strength Data	Field Tests	Index Tests
0									
0-9.5'		Brown, LEAN CLAY, stiff to very hard, moist	855						
5			850					PP = 4.25 tsf Torvane >0.90 tsf	LI = 38 PL = 16 MC = 19.7%
				X	100	4-8-7 (17)		PP = 1.90 tsf	MC = 21.1%
9.5-20'		Gray and brown, LEAN CLAY scattered fine sand, medium stiff to very hard, moist	845					PP = 0.60 tsf Torvane = 0.55 tsf	LL = 28 PL = 15 MC = 26.1%
				X	100	5-6-9 (20)		PP = 0.80 tsf	MC = 20.3%
15			840					PP = 4.30 tsf Torvane = 0.45 tsf	LL = 29 PL = 14 MC = 18.5%
				X	93	5-8-10 (24)	Qu Test Results UCS = 2.32 ksf MC = 18.3% γ _{moist} = 125.9 pcf	PP = 4.50 tsf	MC = 18.8%
20-26.3'		Yellowish brown to orangeish brown, FAT CLAY scattered sand, scattered fine gravel, very hard, moist	835					PP = 6.00 tsf	LL = 42 PL = 16 MC = 18.8%
25			830					PP = 3.50 tsf	
26.3-31.3'		Clay Shale, pale greenish gray, thinly laminated, soft, highly weathered, attempted coring with no recovery.		X					
30			825						
31.3-38'		Clay Shale, dark gray, thinly laminated, soft to medium hard, slightly weathered		X		9-18-28 (61)			
35									

LETTER BORING - MODDOT - 07-29-11.GDT - 4/10/12 13:02 - J:\ISS\GINT\PROJECT FILES\R35G - SKILES.GPJ

N₆₀ = (Em/60)N_m N₆₀ - Corrected N value for standard 60% SPT efficiency, Em - Measured hammer efficiency in percent; N_m - Observed N-value
(1) = Assumed, (2) = Actual

Coordinate System: Modified U.S. State Plane 1983 Coordinate Zone: Missouri Central Coordinate Proj. Factor: _____

Coordinate Datum: NAD 83 (CONUS) Coordinate Units: U.S. Survey Feet

* Persons using this information are cautioned that the materials shown are determined by the equipment noted and accuracy of the "log of materials" is limited thereby and by judgement of the operator. THIS INFORMATION IS FOR DESIGN PURPOSES ONLY.

Missouri Department of Transportation
Construction and Materials

BORING NO. A-12-15
Page 2 of 2

Job No.: R35G - Skiles County: Clay Route: _____
 Design: n/a Skew: _____ Location: near I-435
 Bent: _____ Logged By: George Davis Operator: Michael Donahoe
 Station: _____ Northing: 1090951.5 Date of Work: 02/29/12-02/29/12
 Offset: _____ Easting: 2792846.9 Depth to Water: _____
 Elevation: 855.9 Requested Northing: _____ Depth Hole Open: _____
 Requested Station: _____ Requested Easting: _____ Time Change: _____
 Requested Offset: _____ Equipment: Falling 1500, Split-Spoon Sampler, Shelby Tube
 Requested Elevation: _____ Location Note: Southeast Corner Planned Salt/ Brine Storage Bldg.
 Drill No.: G-7887 Hammer Efficiency: 80% Drilling Method: Mud Rotary

Depth (ft)	Graphic	Description	Elevation (ft)	Sample Type	REC % (RQD %)	Blow Counts (N ₆₀)	Shear Strength Data	Field Tests	Index Tests
35		31.3-38' Clay Shale, dark gray, thinly laminated, soft to medium hard, slightly weathered (continued)	820						
		Bottom of borehole at 38.0 feet.							

LETTER BOREHOLE - MODDOT_07-28-11_GDT - 4/10/12 13:02 - J:\SG\INT\PROJECT FILES\R35G - SKILES.GPJ

$N_{60} = (Em/80)N_m$ N_{60} - Corrected N value for standard 60% SPT efficiency; Em - Measured hammer efficiency in percent; Nm - Observed N-value
 (1) = Assumed, (2) = Actual

Coordinate System: Modified U.S. State Plane 1983 Coordinate Zone: Missouri Central Coordinate Proj. Factor: _____

Coordinate Datum: NAD 83 (CONUS) Coordinate Units: U.S. Survey Feet

* Persons using this information are cautioned that the materials shown are determined by the equipment noted and accuracy of the "log of materials" is limited thereby and by judgement of the operator. THIS INFORMATION IS FOR DESIGN PURPOSES ONLY.

Missouri Department of Transportation
Construction and Materials

BORING NO. V-12-01
Page 1 of 2

Job No.: R35G - Skiles
Design: n/a
Bent: _____
Station: _____
Offset: _____
Elevation: 855.4
Requested Station: _____
Requested Offset: _____
Requested Elevation: _____
Drill No.: G-7887

County: Clay
Skew: _____
Logged By: George Davis
Northing: 1090951.5
Easting: 2792786.9
Requested Northing: _____
Requested Easting: _____
Equipment: Falling 1500 Split-Spoon Sampler, Shelby Tube
Location Note: Northwest Corner Planned Salt/Brine Storage Bldg.
Hammer Efficiency: 80%

Route: _____
Location: near I-435
Operator: Michael Donahce
Date of Work: 03/01/12-03/01/12
Depth to Water: _____
Depth Hole Open: _____
Time Change: _____
Drilling Method: Mud Rotary

Depth (ft)	Graphic	Description	Elevation (ft)	Sample Type	REC % (ROD %)	Blow Counts (N ₆₀)	Shear Strength Data	Field Tests	Index Tests
0			855						
0-9.5'		Light brown mottled gray, LEAN CLAY, very hard, moist							
5			850				Qu Test Results UCS = 6.94 ksf MC = 10.8% γ _{moist} = 126.9 pcf	PP > 9.00 tsf Torvane > 0.90 tsf	MC = 14.8%
					73	4-6-8 (19)		PP = 6.00 tsf	LL = 42 PL = 19 MC = 24.1%
9.5-12.6'		Light gray, LEAN CLAY to silt, very hard, moist, brittle	845					PP = 7.50 tsf Torvane > 0.90 tsf	LL = 26 PL = 19 MC = 9.8%
12.5-15'		Gray and yellow, LEAN CLAY to fat clay, scattered sand, very hard, moist			93	7-8-12 (27)		PP = 6.00 tsf	MC = 17.2%
15-21.1'		Yellowish brown, FAT CLAY scattered sand, very hard, moist	840				Qu Test Results UCS = 13.8 ksf MC = 16.3% γ _{moist} = 132.8 pcf	PP = 7.80 tsf Torvane > 0.90 tsf	MC = 16.5%
					93	5-7-10 (23)		PP = 7.00 tsf	LL = 48 PL = 19 MC = 18.9%
21.1-23.3'		Clay Shale, thinly laminated, no core	835		100	25-38/0.1'	Qu Test Results UCS = 3.88 ksf MC = 34.4% γ _{moist} = 120.9 pcf	PP = 3.50 tsf Torvane > 0.90 tsf PP = 3.25 tsf Torvane > 0.90 tsf	MC = 37.2%
23.3-29.7'		Clay Shale, dark gray, thinly laminated, soft	830				Qu Test Results UCS = 10.94 ksf MC = 14.4% γ _{moist} = 142.7 pcf		
29.7-34.7'		Limestone, gray, thin bedded, hard, fine grained	825		100 (0)				

Bottom of borehole at 34.7 feet.

N₆₀ = (Em/60)Nm N₆₀ - Corrected N value for standard 60% SPT efficiency; Em - Measured hammer efficiency in percent; Nm - Observed N-value
(1) = Assumed, (2) = Actual

Coordinate System: Modified U.S. State Plane 1983 Coordinate Zone: Missouri Central Coordinate Proj. Factor: _____

Coordinate Datum: NAD 83 (CONUS) Coordinate Units: U.S. Survey Feet

* Persons using this information are cautioned that the materials shown are determined by the equipment noted and accuracy of the "log of materials" is limited thereby and by judgment of the operator. THIS INFORMATION IS FOR DESIGN PURPOSES ONLY.

LETTER BOREHOLE - MODOT_07-28-11.GDT - 4/10/12 13:02 - J:\S\GANT\PROJECT FILES\R35G - SKILES.GPJ

Missouri Department of Transportation
Construction and Materials

BORING NO. V-12-01
Page 2 of 2

Job No.: R35G - Skiles
Design: n/a
Bent: _____
Station: _____
Offset: _____
Elevation: 855.4
Requested Station: _____
Requested Offset: _____
Requested Elevation: _____
Drill No.: G-7887

County: Clay
Skew: _____
Logged By: George Davis
Northing: 1090951.5
Easting: 2792786.9
Requested Northing: _____
Requested Easting: _____
Equipment: Failing 1500 Split-Spoon Sampler, Shelby Tube
Location Note: Northwest Corner Planned Salt/Brine Storage Bldg.
Hammer Efficiency: 80%

Route: _____
Location: near I-435
Operator: Michael Conahoe
Date of Work: 03/01/12-03/01/12
Depth to Water: _____
Depth Hole Open: _____
Time Change: _____
Drilling Method: Mud Rotary

Depth (ft)	Graphic	Description	Elevation (ft)	Sample Type REC % (ROD %)	Blow Counts (N ₆₀)	Shear Strength Data	Field Tests	Index Tests
				100 (72)		Qu Test Results UCS = 373.54 ksf MC = 0% γ _{max} = 165.7 pcf		

LETTER BOREHOLE - MODDOT_07-28-11.GDT - 4/10/12 13:02 - J:\SIG\INT\PROJECT FILES\R35G - SKILES.GPJ

$N_{60} = (Em/60)N_m$ N_{60} - Corrected N value for standard 60% SPT efficiency; Em - Measured hammer efficiency in percent; Nm - Observed N-value
(1) = Assumed, (2) = Actual

Coordinate System: Modified U.S. State Plane 1983 Coordinate Zone: Missouri Central Coordinate Proj. Factor: _____
Coordinate Datum: NAD 83 (CONUS) Coordinate Units: U.S. Survey Feet

* Persons using this information are cautioned that the materials shown are determined by the equipment noted and accuracy of the "log of materials" is limited thereby and by judgement of the operator. THIS INFORMATION IS FOR DESIGN PURPOSES ONLY.

Missouri Department of Transportation
Construction and Materials

BORING NO. V-12-02
Page 1 of 2

Job No.: R35G - Skiles
 Design: n/a
 Bent: _____
 Station: _____
 Offset: _____
 Elevation: 858.2
 Requested Station: _____
 Requested Offset: _____
 Requested Elevation: _____
 Drill No.: G-7950

County: Clay
 Skew: _____
 Logged By: Steve Owens
 Northing: 1091051.5
 Easting: 2792846.9
 Requested Northing: _____
 Requested Easting: _____
 Equipment: CME 850, Continuous Sampler, Split-Spoon Sampler
 Location Note: Northeast Corner Planned Salt/Brine Storage Bldg.
 Hammer Efficiency: 79%

Route: _____
 Location: near I-435
 Operator: Michael Donahoe
 Date of Work: 03/05/12
 Depth to Water: 0
 Depth Hole Open: 17.4
 Time Change: 2 days
 Drilling Method: Mud Rotary

Depth (ft)	Graphic	Description	Elevation (ft)	Sample Type	REC % (RQD %)	Blow Counts (N ₆₀)	Shear Strength Data	Field Tests	Index Tests
0		0-21.7' Brown, LEAN CLAY, very stiff, moist	855						
5			850		16	7-9-10 (25)		PP > 4.50 tsf Torvane > 0.90 tsf	MC = 14.9%
10			845		84	6-11-11 (29)		PP > 4.50 tsf Torvane > 0.90 tsf	MC = 9.6% LL = 24 PL = 17
15			840		100	8-10-12 (29)	Qu Test Results UCS = 6.94 ksf MC = 16.6% γ _{moist} = 126.5 pcf	PP = 4.50 tsf Torvane > 0.90 tsf	MC = 17.3% LL = 36 PL = 16
20			835		56	6-9-12 (28)		PP = 4.50 tsf Torvane > 0.90 tsf	MC = 28.9%
25		21.7-25' Grayish brown, FAT CLAY, very stiff, moist						PP = 4.50 tsf	
25		25-28.4' Shale, greenish gray, thinly laminated, soft			56			PP = 4.50 tsf Torvane > 0.90 tsf	
30		28.4-33.6' Limestone, gray, thin bedded, moderately hard, fine grained	830			7-37, 10/0'		PP = 4.50 tsf	
35		33.6-38.4' Shale, gray, thinly laminated, soft	825		40 (0)		Qu Test Results UCS = 18.28 ksf		

LETTER BORING - MODDOT_07-29-11.GDT - 4/10/12 13:02 - J:\S\G\PROJECT FILES\R35G - SKILES.GPJ

$N_{60} = (E_m/60)N_m$ N_{60} - Corrected N value for standard 60% SPT efficiency, E_m - Measured hammer efficiency in percent; N_m - Observed N-value
 (1) = Assumed, (2) = Actual

Coordinate System: Modified U.S. State Plane 1983 Coordinate Zone: Missouri Central Coordinate Proj. Factor: _____

Coordinate Datum: NAD 83 (CONUS) Coordinate Units: U.S. Survey Feet

* Persons using this information are cautioned that the materials shown are determined by the equipment noted and accuracy of the "log of materials" is limited thereby and by judgement of the operator. THIS INFORMATION IS FOR DESIGN PURPOSES ONLY.

Missouri Department of Transportation
Construction and Materials

BORING NO. V-12-02
Page 2 of 2

Job No.: R35G - Skiles County: Clay Route: _____
 Design: n/a Skew: _____ Location: near I-435
 Bent: _____ Logged By: Steve Owens Operator: Michael Donahoe
 Station: _____ Northing: 1091051.5 Date of Work: 03/05/12
 Offset: _____ Easting: 2792846.9 Depth to Water: 0
 Elevation: 858.2 Requested Northing: _____ Depth Hole Open: 17.4
 Requested Station: _____ Requested Easting: _____ Time Change: 2 days
 Requested Offset: _____ Equipment: CME 850, Continuous Sampler, Split-Spoon Sampler
 Requested Elevation: _____ Location Note: Northeast Corner Planned Salt/Brine Storage Bldg.
 Drill No.: G-7950 Hammer Efficiency: 79% Drilling Method: Mud Rotary

Depth (ft)	Graphic	Description	Elevation (ft)	Sample Type	REC % (ROD %)	Blow Counts (N ₆₀)	Shear Strength Data	Field Tests	Index Tests
35		33.6-38.4' Shale, gray, thinly laminated, soft (continued)	820		40 (0)		MC = 13.3% γ _{moist} = 139.9 pcf		
		Bottom of borehole at 38.4 feet.							

LETTER BOREHOLE - MODDT - 07-29-11.GDT - 4/10/12.1302 - J:\SSG\INT\PROJECT FILES\R35G - SKILES.GPJ

N₆₀ = (Em/60)Nm N₆₀ - Corrected N value for standard 60% SPT efficiency; Em - Measured hammer efficiency in percent; Nm - Observed N-value
 (1) = Assumed, (2) = Actual

Coordinate System: Modified U.S. State Plane 1983 Coordinate Zone: Missouri Central Coordinate Proj. Factor: _____
 Coordinate Datum: NAD 83 (CONUS) Coordinate Units: U.S. Survey Feet

* Persons using this information are cautioned that the materials shown are determined by the equipment noted and accuracy of the "log of materials" is limited thereby and by judgement of the operator. THIS INFORMATION IS FOR DESIGN PURPOSES ONLY.

Missouri Department of Transportation
Construction and Materials

BORING NO. V-12-03
Page 1 of 1

Job No.: R35G - Skiles
Design: n/a
Bent: _____
Station: _____
Offset: _____
Elevation: 855.2
Requested Station: _____
Requested Offset: _____
Requested Elevation: _____
Drill No.: G-7950

County: Clay
Skew: _____
Logged By: Steve Owens
Northing: 1090951.5
Easting: 2792786.9
Requested Northing: _____
Requested Easting: _____
Hammer Efficiency: 79%

Route: _____
Location: near I-435
Operator: Michael Donahoe
Date of Work: 03/06/12
Depth to Water: 6.2
Depth Hole Open: 12
Time Change: 24 hours
Equipment: CME 850, Continuous Sampler, Split-Spoon Sampler
Location Note: Southwest Corner Planned Salt/Brine Storage Bldg.
Drilling Method: Mud Rotary

Depth (ft)	Graphic	Description	Elevation (ft)	Sample Type	REC % (RQD %)	Blow Counts (N ₆₀)	Shear Strength Data	Field Tests	Index Tests
0			855						
0-20'		Brown, LEAN CLAY, very stiff, moist							
5			850		36			PP = 4.00 tsf Torvane = 0.90 tsf	MC = 18.4% LL = 29 PL = 16
						4-5-8 (17)		PP = 4.00 tsf	
10			845		68		Qu Test Results UCS = 2.32 ksf MC = 21.2% γ _{moist} = 124.2 pcf	PP = 3.75 tsf Torvane = 0.90 tsf	MC = 18.3% LL = 22 PL = 18
						4-8-8 (18)		PP = 4.50 tsf Torvane >0.90 tsf	
15			840		72			PP = 4.50 tsf Torvane >0.90 tsf	MC = 18.1%
						5-9-8 (22)			
20		20-21.4' Tannish green, FAT CLAY, very stiff, moist	835		56			PP = 4.50 tsf Torvane >0.90 tsf	MC = 31.5%
		21.4-27.6' Shale, tannish green, thinly laminated, soft				19-37, 10/0'		PP = 4.50 tsf	
25			830		100 (0)		Qu Test Results UCS = 2.74 ksf MC = 18.6% γ _{moist} = 134.8 pcf		
		Bottom of borehole at 27.6 feet.							

LETTER BOREHOLE - MDCDOT_07-29-11.GDT - 4/10/12 13:02 - J:\S\G\INT\PROJECT FILES\R35G - SKILES.GPJ

$N_{60} = (Em/60)Nm$ N_{60} - Corrected N value for standard 60% SPT efficiency; Em - Measured hammer efficiency in percent; Nm - Observed N-value
(1) = Assumed, (2) = Actual

Coordinate System: Modified U.S. State Plane 1983 Coordinate Zone: Missouri Central Coordinate Proj. Factor: _____
Coordinate Datum: NAD 83 (CONUS) Coordinate Units: U.S. Survey Feet

* Persons using this information are cautioned that the materials shown are determined by the equipment noted and accuracy of the "log of materials" is limited thereby and by judgement of the operator. THIS INFORMATION IS FOR DESIGN PURPOSES ONLY.

Missouri Department of Transportation
Construction and Materials

BORING NO. V-12-04
Page 1 of 1

Job No.: R35G - Skiles
Design: n/a
Bent: _____
Station: _____
Offset: _____
Elevation: 860
Requested Station: _____
Requested Offset: _____
Requested Elevation: _____
Drill No.: G-7950

County: Clay
Skew: _____
Logged By: Steve Owens
Northing: 1091288.7
Easting: 2792862.9
Requested Northing: _____
Requested Easting: _____
Hammer Efficiency: 79%

Route: _____
Location: near I-435
Operator: Michael Donahoe
Date of Work: _____
Depth to Water: _____
Depth Hole Open: 0
Time Change: _____
Equipment: CME 850, Continuous Sampler, Split-Spoon Sampler
Location Note: Northwest Corner Planned Maintenance Main Bldg.
Drilling Method: Mud Rotary

Depth (ft)	Graphic	Description	Elevation (ft)	Sample Type	REC % (RCD %)	Blow Counts (N ₆₀)	Shear Strength Data	Field Tests	Index Tests
0			860						
0-29.2'		Brown, LEAN CLAY, very stiff, moist							
5			855		64			PP = 4.50 tsf Torvane = 0.90 tsf	MC = 17.0% LL = 31 PL = 19
10			850			9-10-10 (26)			
15			845		96	6-7-7 (18)	Cu Test Results	PP = 4.50 tsf Torvane = 0.35 tsf	MC = 12.6% LL = 28 PL = 20 LL = 25 PL = 20
20			840			8-8-9 (22)		PP = 4.50 tsf	
25			835			2-6-8 (16)		PP = 3.00 tsf	
						3-5-8 (17)		PP = 3.00 tsf	
29.2-34.5'		Limestone, gray, thin bedded, 29.2-29.8' cut with rock bit			64		Cu Test Results UCS = 507.74 ksf MC = 0% $\gamma_{moist} = 165.4$ pcf		

Bottom of borehole at 29.0 feet

$N_{60} = (E_m/60)N_m$ N_{60} - Corrected N value for standard 60% SPT efficiency; E_m - Measured hammer efficiency in percent; N_m - Observed N-value
(1) = Assumed, (2) = Actual

Coordinate System: Modified U.S. State Plane 1983 Coordinate Zone: Missouri Central Coordinate Proj. Factor: _____
Coordinate Datum: NAD 83 (CONUS) Coordinate Units: U.S. Survey Feet

* Persons using this information are cautioned that the materials shown are determined by the equipment noted and accuracy of the 'log of materials' is limited thereby and by judgement of the operator. THIS INFORMATION IS FOR DESIGN PURPOSES ONLY.

LETTER BOREHOLE - MOODY 07-28-11.LGDY - 4/10/12 13:02 - J:\SIG\INT\PROJECT FILES\R35G - SKILES.GPJ

Missouri Department of Transportation
Construction and Materials

BORING NO. V-12-05
Page 1 of 1

Job No.: R35G - Skiles
 Design: n/a
 Bent: _____
 Station: _____
 Offset: _____
 Elevation: 859.2
 Requested Station: _____
 Requested Offset: _____
 Requested Elevation: _____
 Drill No.: G-7950

County: Clay
 Skew: _____
 Logged By: Steve Owens
 Northing: 1091238.7
 Easting: 2792862.9
 Requested Northing: _____
 Requested Easting: _____
 Equipment: CME 850, Continuous Sampler, Split-Spoon Sampler
 Location Note: Southwest Corner Planned Maintenance Main Bldg.
 Hammer Efficiency: 79%

Route: _____
 Location: near I-435
 Operator: Michael Donahoe
 Date of Work: 03/06/12
 Depth to Water: _____
 Depth Hole Open: 13.5
 Time Change: 16 hours
 Drilling Method: Mud Rotary

Depth (ft)	Graphic	Description	Elevation (ft)	Sample Type	REC % (ROD %)	Blow Counts (N ₆₀)	Shear Strength Data	Field Tests	Index Tests
0		0-23' Brown, LEAN CLAY, very stiff, moist							
5			855		96			PP = 4.50 tsf Torvane >0.90 tsf	MC = 11.8% LL = 28 PL = 21
10			850			6-6-8 (20)		PP = 4.50 tsf	
16			845		88	4-5-8 (14)	Cu Test Results UCS = 10.1 ksf MC = 13.6% Y _{moist} = 125.7 pcf	PP = 4.50 tsf Torvane = 0.90 tsf	MC = 12.9% LL = 28 PL = 21
20			840		96	5-7-9 (21)		PP = 4.50 tsf Torvane >0.90 tsf	MC = 17.5%
25		23-29' Shale, tannish green, thinly laminated, soft, 23.0-24.0 rock bit.	835		92	3-6-7 (17)		PP = 4.50 tsf Torvane >0.90 tsf	MC = 16.2%
		Bottom of borehole at 29.0 feet.			100		Cu Test Results UCS = 5.32 ksf MC = 27.5% Y _{moist} = 123.1 pcf	PP = 4.50 tsf	

LETTER BOREHOLE - MOC DOT - 07-28-11.GDT - 4/10/12 13:02 - J:\SIGINT\PROJECT FILES\R35G - SKILES.GPJ

N₆₀ = (Em/60)Nm N₆₀ - Corrected N value for standard 60% SPT efficiency; Em - Measured hammer efficiency in percent; Nm - Observed N-value
 (1) = Assumed, (2) = Actual

Coordinate System: Modified U.S. State Plane 1983 Coordinate Zone: Missouri Central Coordinate Proj. Factor: _____
 Coordinate Datum: NAD 83 (CONUS) Coordinate Units: U.S. Survey Feet

* Persons using this information are cautioned that the materials shown are determined by the equipment noted and accuracy of the "log of materials" is limited thereby and by judgement of the operator. THIS INFORMATION IS FOR DESIGN PURPOSES ONLY.

Missouri Highways and Transportation Commission
Standard Bid/Proposal Provisions, General Terms and Conditions and Special Terms and Conditions

STANDARD SOLICITATION PROVISIONS

- a. The solicitation for the procurement of the supplies referenced therein, to which these "Standard Bid Provisions, General Terms and Conditions and Special Terms and Conditions" are attached, is being issued under, and governed by, the provisions of Title 7 – Missouri Department of Transportation, Division 10 – Missouri Highways and Transportation Commission, Chapter 11 – Procurement of Supplies, of the Code of State Regulations. The Missouri Highways and Transportation Commission (MHTC), acting by and through its operating arm, the Missouri Department of Transportation (MoDOT), draws the Bidder's attention to said 7 CSR 10-11 for all the provisions governing solicitation and receipt of bids/quotes and the award of the contract pursuant to this solicitation.
- b. All bids/quotes must be signed with the firm name and by a responsible officer or employee. Obligations assumed by such signature must be fulfilled.

GENERAL TERMS AND CONDITIONS

Definitions

Capitalized terms as well as other terms used but not defined herein shall have the meaning assigned to them in section 7 CSR 10-11.010 Definition of Terms.

Nondiscrimination

- a. The Contractor shall comply with all state and federal statutes applicable to the Contractor relating to nondiscrimination, including, but not limited to, Chapter 213, RSMo; Title VI and Title VII of Civil Rights Act of 1964 as amended (42 U.S.C. Sections 2000d and 2000e, *et seq.*); and with any provision of the "Americans with Disabilities Act" (42 U.S.C. Section 12101, *et seq.*).
- b. **Sanctions for Noncompliance:** In the event of the Contractor's noncompliance with the nondiscrimination provisions of this contract, MHTC shall impose such contract sanctions as it or the Federal Highway Administration may determine to be appropriate, including, but not limited to:
 - i. withholding of payments to the Contractor under the contract until the Contractor complies, and/or,
 - ii. cancellation, termination or suspension of the contract, in whole or in part.

Contract/Purchase Order

- a. By submitting a bid/quote, the Bidder agrees to furnish any and all equipment, supplies and/or services specified in the solicitation documents, at the prices quoted, pursuant to all requirements and specifications contained therein.
- b. A binding contract shall consist of: (1) the solicitation documents, amendments thereto, and/or Best and Final Offer (BAFO) request(s) with any changes/additions, (2) the Contractor's bid response, and (3) the MHTC's acceptance of the bid by post-award contract or purchase order.
- c. A notice of award does not constitute an authorization for shipment of equipment or supplies or a directive to proceed with services. Before providing equipment, supplies and/or services, the Contractor must receive a properly authorized notice to proceed and/or purchase order.

Applicable Laws and Regulations

- a. The contract shall be construed according to the laws of the State of Missouri. The Contractor shall comply with all local, state, and federal laws and regulations related to the performance of the contract. The exclusive venue for any legal proceeding relating to or arising, out of the contract shall be in the Circuit Court of Cole County, Missouri.
- b. The Contractor must be registered and maintain good standing with the Secretary of State of the State of Missouri, Missouri Department of Revenue, and other regulatory agencies, as may be required by law or regulations. Prior to the issuance of a purchase order and/or notice to proceed, the Contractor may be required to submit to MHTC a copy of their current Authority Certificate from the Secretary of State of the State of Missouri and/or a copy of their Certificate of No Tax Due from the Missouri Department of Revenue.
- c. Prior to the issuance of a purchase order and/or notice to proceed, all **out-of-state** Contractors **providing services** within the state of Missouri must submit to MHTC a copy of their current Transient Employer Certificate from the Missouri Department of Revenue, in addition to a copy of their current Authority Certificate from the Secretary of State of the State of Missouri.

Executive Order:

The Contractor shall comply with all the provisions of Executive Order 07-13, issued by the Honorable Matt Blunt, Governor of Missouri, on the sixth (6th) day of March, 2007. This Executive Order, which promulgates the State of Missouri's position to not tolerate persons who contract with the state engaging in or supporting illegal activities of employing individuals who are not eligible to work in the United States, is incorporated herein by reference and made a part of this Agreement.

- 1) "By signing this Agreement, the Contractor hereby certifies that any employee of the Contractor assigned to perform services under the contract is eligible and authorized to work in the United States in compliance with federal law."
- 2) In the event the Contractor fails to comply with the provisions of the Executive Order 07-13, or in the event the Commission has reasonable cause to believe that the contractor has knowingly employed individuals who are not eligible to work in the United States in violation of federal law, the Commission reserves the right to impose such contract sanctions as it may determine to be appropriate, including but not limited to contract cancellation, termination or suspension in whole or in part or both.
- 3) The Contractor shall include the provisions of this paragraph in every subcontract. The Contractor shall take such action with respect to any subcontract as the Commission may direct as a means of enforcing such provisions, including sanctions for noncompliance.

Preferences

- a. In the evaluation of bids/quotes, preferences shall be applied in accordance with 7 CSR 10-11.020(7). Contractors should apply the same preferences in selecting subcontractors. The attached document entitled "**VENDOR INFORMATION AND PREFERENCE CERTIFICATION FORM**" must be completed and returned with the solicitation documents.
- b. Bidders are encouraged to obtain minority business enterprise (MBE) and women business enterprise (WBE) participation in this work through the use of subcontractors, suppliers, joint ventures, or other arrangements that afford meaningful participation for M/WBEs. Bidders are encouraged to obtain 10% MBE and 5% WBE participation.

Missouri Highways and Transportation Commission
Standard Bid/Proposal Provisions, General Terms and Conditions and Special Terms and Conditions

Cancellation of Contract

The MHTC may cancel the Contract at any time for a material breach of contractual obligations or for convenience by providing Contractor with written notice of cancellation. Should the MHTC exercise its right to cancel the contract for such reasons, cancellation will become effective upon the date specified in the notice of cancellation sent to the Contractor.

Bankruptcy or Insolvency

Upon filing for any bankruptcy or insolvency proceeding by or against the Contractor, whether voluntarily, or upon the appointment of a receiver, trustee, or assignee, for the benefit of creditors, the Commission reserves the right and sole discretion to either cancel the Agreement or affirm the Agreement and hold the Contractor responsible for damages.

Warranty

The Contractor expressly warrants that all equipment, supplies, and/or services provided shall: (1) conform to each and every specification, drawing, sample or other description which was furnished to or adopted by the MHTC, (2) be fit and sufficient for the purpose expressed in the solicitation documents, (3) be merchantable, (4) be of good materials and workmanship, and (5) be free from defect.

Status of Independent Contractor

The Contractor represents itself to be an independent Contractor offering such services to the general public and shall not represent itself or its employees to be an employee of the MHTC. Therefore, the Contractor shall assume all legal and financial responsibility for taxes, FICA, employee fringe benefits, workers' compensation, employee insurance, minimum wage requirements, overtime, etc., and agrees to indemnify, save and hold the MHTC, its officers, agents and employees harmless from and against any and all losses (including attorney fees) and damage of any kind related to such matters.

Non-Waiver

If one of the parties agrees to waive its right to enforce any term of this Contract, that party does not waive its right to enforce such term at any other time or to enforce any or all other terms of this Contract.

Indemnification

The Contractor shall defend, indemnify and hold harmless MHTC, including its members and department employees, from any claim or liability whether based on a claim for damages to real or personal property or to a person for any matter relating to or arising out of the Contractor's performance of its obligations under the contract awarded pursuant to this solicitation.

SPECIAL TERMS AND CONDITIONS

Tax Exempt Status:

MHTC is exempt from paying Missouri Sales Tax, Missouri Use Tax and Federal Excise Tax. However, the Contractor may themselves be responsible for the payment of taxes on materials they purchase to fulfill the contract. A Project Tax Exemption Certificate will be furnished to the successful Bidder upon request if applicable.

Insurance

The Contractor shall maintain or cause to be maintained at Contractor's own expense commercial general liability, automobile liability, worker's compensation insurance against negligent acts, errors or omissions of the Contractor, or its subcontractors and anyone directly or indirectly employed by any of them. Any insurance policy required as specified in this Section shall be written by a company that is licensed and authorized to issue such insurance in the state of Missouri and shall provide insurance coverage for not less than the following limits of liability:

- 1) General Liability: Not less than \$500,000 for any one person in a single accident or occurrence, and not less than \$3,000,000 for all claims arising out of a single occurrence;
- 2) Automobile Liability: Not less than \$500,000 for any one person in a single accident or occurrence, and not less than \$3,000,000 for all claims arising out of a single occurrence;
- 3) Missouri State Workmen's Compensation policy or equivalent in accordance with state law.

Upon request from the Commission, the Contractor shall provide the Commission with certificates of insurance evidencing the required coverage and that such insurance is in effect.

Bid Guaranty/Contract Bond

- a. Each bid shall be accompanied by a Bid Bond, Certified Check, Cashier's Check or Bank Money Order payable to the Director of Revenue – Credit State Road Fund for an amount equal to Five Percent (5%) of the amount of the bid submitted (the largest total combined bid amount including alternate bid amounts). This is to act as a guarantee that the bidder, if awarded the contract, will furnish an acceptable performance and payment bond (Contract Bond) or a cashier's check, a bank money order or a certified check made payable to "Director of Revenue--Credit State Road Fund" in an amount equal to One Hundred (100%) of the contract price.
- b. If a BID BOND is used (in lieu of a certified check, cashier's check, or bank money order), it must be in the form provided and executed by the bidder as principal and by a surety company authorized to do business in the State of Missouri as surety. The agent executing the same on behalf of the surety company must attach a current Power of Attorney setting forth his authority to execute the bond involved.
- c. Certified Checks, Cashier's Checks or Bank Money Orders of unsuccessful bidders will be returned as soon as the award is made. The checks or bank money orders of the successful bidder(s) will be retained until the contract is executed and a satisfactory Performance and Payment (Contract Bond) is furnished. Bid Bonds will not be returned except on specific request of the bidder.

Missouri Highways and Transportation Commission

Standard Bid/Proposal Provisions, General Terms and Conditions and Special Terms and Conditions

- d. Failure to execute the contract and file acceptable performance payment (Contract Bond) or cashier's check, bank money order or certified check within 15 days after the contract has been mailed to the bidder shall be just cause for the cancellation of the award and the forfeiture of the proposal guaranty. Award may then be made to the next lowest responsible bidder, or the work may be re-advertised and performed under contract or otherwise, as the Commission may decide. No contract shall be considered effective until it has been executed by all parties thereto.

Subcontracting

- a. It is specifically understood that no portion of the material or any interest in the contract, shall be subcontracted, transferred, assigned or otherwise disposed of, except with the written consent of MHTC. Request for permission to subcontract or otherwise dispose of any part of the work shall be in writing to MHTC and accompanied by documentation showing that the organization which will perform the work is particularly experienced and equipped for such work.
- b. Consent to subcontract or otherwise dispose of any portion of the work shall not be construed to relieve the Contractor of any responsibility for the production and delivery of the contracted work and the completion of the work within the specified time.
- c. All payments for work performed by a subcontractor shall be made to the Contractor to whom the contract was awarded and the purchase order issued.

Prohibition Of Employment Of Unauthorized Aliens:

- a. **Non-employment of Unauthorized Aliens:** Pursuant to Section 285.530, RSMo., no business entity or employer shall knowingly employ, hire for employment, or continue to employ an unauthorized alien to perform work within the State of Missouri. As a condition for the award of any contract or grant in excess of five thousand dollars by the State or by any political subdivision of the State to a business entity, or for any business entity receiving a state-administered or subsidized tax credit, tax abatement, or loan from the state, the business entity shall:
 - 1) By sworn affidavit and provision of documentation, affirm its enrollment and participation in a federal work authorization program with respect to the employees working in connection with the contracted services. E-Verify is an example of a federal work authorization program. The business entity must affirm its enrollment and participation in the E-Verify federal work authorization program with respect to the employees proposed to work in connection with the services requested herein by providing acceptable enrollment and participation documentation consisting of **completed** copy of the E-Verify Memorandum of Understanding (MOU). For business entities that are not already enrolled and participating in a federal work authorization program, E-Verify is available at http://www.dhs.gov/files/programs/qc_1185221678150.shtm
 - 2) By sworn affidavit, affirm that it does not knowingly employ any person who is an unauthorized alien in connection with the contracted services. A copy of the affidavit referenced herein is provided within this document, attached as Exhibit A.
- b. **Proof of Lawful Presence For Sole Proprietorships and Partnerships:** If the business entity is a sole proprietorship or partnership, pursuant to Section 208.009, RSMo., each sole proprietor and each general partner shall provide affirmative proof of lawful presence in the United States. Such sole proprietorship or partnership is eligible for temporary public benefits upon submission by each sole proprietor and general partner of a sworn affidavit of his/her lawful presence on the United States until such lawful presence is affirmatively determined, or as otherwise provided by Section 208.009, RSMo. A copy of the affidavit reference herein is provided within this document, attached as Exhibit B.

Construction Safety Program

Missouri law, 292.675 RSMo, requires the awarded Contractor and its subcontractor(s) to provide a ten-hour occupational safety and health administration (OSHA) construction safety program (or a similar program approved by the Missouri Department of Labor and Industrial Relations as a qualified substitute) for their on-site employees (laborers, workmen, drivers, equipment operators, and craftsmen) who have not previously completed such a program and are directly engaged in actual construction of the improvement (or working at a nearby or adjacent facility used for construction of the improvement). The Contractor and its subcontractor(s) shall require all such employees to complete this ten-hour program, pursuant to 292.675 RSMo, unless they hold documentation on their prior completion of said program. Penalties for non-compliance include Contractor forfeiture to the Commission in the amount of \$2,500, plus \$100 per contractor and subcontractor employee for each calendar day such employee is employed beyond the elapsed time period for required program completion under 292.675 RSMo.

Prevailing Wage

- a. The work to be performed under this solicitation is governed by the provisions of Chapter 290 RSMo, as amended, related to prevailing wages to be paid on public works.
- b. If the bid/quote is accepted, the vendor will be required to comply with the prevailing wages as fixed by the Missouri Department of Labor and Industrial Relations, in effect as of the date of the issuance of the solicitation, for each affected craft and type of workmen in the following county(ies): **Statewide**. The **Annual Wage Order #18, Incremental Increase #7** is attached to the bid documents. Pursuant to the requirements of the Chapter 290 RSMo., not less than the prevailing hourly rate of wages, as set out in the wage order attached to and made part of the specification for work under the contract, must be paid to all workers performing work under the contract.
- c. The Contractor shall provide all information, reports and other documentation as required by MHTC to ensure compliance with Chapter 290 RSMo., as amended, relating to prevailing wages to be paid on public works.
- d. The Contractor shall forfeit a penalty to the contracting public body of \$500 per day (or portion of a day) for each worker that is paid less than the prevailing rate for any work done under the contract by the contractor or by any subcontractor.

Permits, Licenses and Safety Issues

The contract price shall include any necessary permits and licenses required by law incidental to the work. Local ordinances requiring building permits are not applicable to state agencies.

Missouri Highways and Transportation Commission
Standard Bid/Proposal Provisions, General Terms and Conditions and Special Terms and Conditions

Liquidated Damages

- a. In the event the successful Contractor fails to deliver the material within the time specified, the Department and the public will sustain damages because of such delay in delivery, the exact extent of which would be difficult to ascertain, and in order to liquidate such damage in advance it is agreed that the **sum of \$500 per day**, for each assessable calendar day on which the delivery has not been completed, is reasonable and the best estimate which the parties can arrive at as liquidated damages, and it is therefore agreed that said amount will be withheld from payments due the Contractor or otherwise collected from the Contractor as liquidated damages.
- b. **Saturdays, Sundays, holidays and days whereas the Department has suspended work shall not be assessable days.**

Time of Completion

If this bid is accepted, it is hereby agreed that work will begin after the "Notice to Proceed" date that is anticipated to be not later than May 25, 2012 and will diligently be prosecuted in order to complete the work and billing by July 1, 2012. Completion of work will be based on FINAL ACCEPTANCE of the work; "SUBSTANTIAL COMPLETION" will not be accepted as basis for completion.